


ALEX W. MCCOY ET AL.  
Berns No. 1.

SEC. 29 T. 22 R. 6E  
SEC NW NE

29-22-6E

Total Depth. 3065  
Comm. 4-19-39 Comp. 5-31-39  
Shot or Treated.  
Contractor. Rox and Morris  
Issued 6-17-39

County Chaso



CASING.

15 1/2" 150' pulled.  
12 1/2" 900' pulled.  
10" 1792' pulled. UR 1829  
8 1/4" 2744' pulled.  
6 5/8" 2925' pulled. UR 3032

Elevation. ?

Production. DRY

Figures Indicate Bottom of Formations.

|                  |      |                     |      |                     |      |
|------------------|------|---------------------|------|---------------------|------|
| lime             | 25   | lime                | 1080 | lime                | 2314 |
| clay             | 55   | shale               | 1105 | shale               | 2317 |
| red rock         | 70   | lime                | 1120 | lime                | 2322 |
| clay yellow      | 90   | shale               | 1155 | shale               | 2415 |
| shale blue       | 95   | lime                | 1180 | lime hole caving    | 2435 |
| lime sdy         | 120  | shale               | 1225 | shale               | 2470 |
| lime             | 145  | lime                | 1250 | hole caving         | 2455 |
| 10 BWPFR 120-145 |      | shale               | 1255 | lime                | 2480 |
| shale            | 150  | lime                | 1265 | shale               | 2515 |
| shale sdy        | 190  | 1/2 BWPFR 1240-45   |      | brokon lime         | 2555 |
| 4 BW 170-190     |      | shale               | 1275 | shale               | 2560 |
| shale            | 205  | lime                | 1295 | lime                | 2570 |
| red rock         | 208  | shale               | 1315 | shale               | 2585 |
| lime             | 213  | lime                | 1320 | lime broken         | 2615 |
| shale lime       | 220  | shale               | 1335 | shale               | 2630 |
| shale            | 225  | lime                | 1370 | shale blk           | 2655 |
| lime             | 230  | shale               | 1380 | lime                | 2660 |
| shale            | 245  | hole caving.        |      | shale blk           | 2680 |
| lime             | 255  | lime                | 1395 | lime broken         | 2685 |
| lime broken      | 295  | shale               | 1410 | shale blk           | 2690 |
| 1 BWPFR 255-265  |      | lime                | 1420 | shale               | 2705 |
| total 5 BWPFR    |      | shale               | 1450 | lime                | 2710 |
| 1 BWPFR 285-295  |      | lime                | 1460 | shale               | 2715 |
| Total 6 BWPFR    |      | shale               | 1480 | lime                | 2722 |
| shale            | 300  | lime                | 1500 | shale               | 2725 |
| red rock         | 305  | shale               | 1555 | lime                | 2730 |
| lime shells and  |      | lime                | 1595 | shale cherty sdy    | 2740 |
| shale            | 355  | shale               | 1600 | cave                |      |
| shale            | 365  | lime                | 1605 | shale cherty        | 2755 |
| lime             | 370  | lime broken         | 1625 | shale dark          | 2770 |
| shale lime       | 395  | shale sdy           | 1640 | shale cherty        | 2798 |
| shale and shells | 435  | 3 1/2 BWPFR 1625-50 |      | lime Miss.          | 2823 |
| shale            | 455  | Total 4 BWPFR       |      | lime                | 2935 |
| lime             | 480  | shale               | 1650 | 1/2 BWPFR 2845-2860 |      |
| shale            | 485  | lime                | 1660 | Hole caving         | 2875 |
| shale lime       | 525  | shale               | 1690 | 3 BWPFR 2900        |      |
| shale            | 535  | 5 BWPFR 1690-1705   |      | lime                | 2945 |
| lime shale       | 545  | total 9 BWPFR       |      | HFW                 |      |
| shale and shells | 595  | sand                | 1705 | lime soft           | 2948 |
| shale            | 670  | shale               | 1775 | shale               | 3043 |
| red rock         | 675  | lime                | 1780 | HFW 3042-3044       |      |
| shale            | 690  | shale               | 1813 | lime                | 3065 |
| lime             | 695  | lime                | 1834 | Total Depth.        |      |
| shale            | 730  | HFW 1813-17'        |      |                     |      |
| red rock         | 735  | shale               | 1885 |                     |      |
| shale            | 745  | lime                | 1987 |                     |      |
| red rock         | 750  | hole caving         | 1945 |                     |      |
| shale            | 880  | 1 BWPFR 1975-87     |      |                     |      |
| 3 BW 780-790     |      | shale               | 2000 |                     |      |
| total 9 BWPFR    |      | shale sdy           | 2030 |                     |      |
| lime             | 885  | shale               | 2170 |                     |      |
| shale            | 910  | lime                | 2195 |                     |      |
| lime             | 920  | shale red rock      | 2205 |                     |      |
| shale lime       | 940  | lime sdy            | 2230 |                     |      |
| lime             | 960  | shale               | 2235 |                     |      |
| shale            | 1000 | lime                | 2270 |                     |      |
| lime             | 1010 | shale blk           | 2275 |                     |      |
| shale            | 1025 | lime                | 2300 |                     |      |
| lime and shale   | 1070 | shale               | 2305 |                     |      |

2948  
2730  
218