

Started 1/11/22, Comp. 3/19/22
 Production first 24 hours 200-bbls. or more.
 T. D. 2246'

Sandoma Oil Co.,
 Jacob Ott Well No. 1.
 Se. Cor S $\frac{1}{2}$ NW $\frac{1}{4}$ Sec. 7-22-13E., Greenwood Co

1-22-13E

*Plate
L.R.*

Lime white hard	15
shale light soft	80
lime white hard	120
shale dark soft	165
lime white hard	175
shale dark soft	205
lime white hard	220
shale dark soft	275
red rock soft	290
lime light hard	300
shale white soft	390
lime gray hard	440
shale light soft	653
sand white soft water	700
lime white hard	860
shale dark soft	910
lime white hard 10 BA 985	1030
shale dark soft	1060
lime white hard, oil water	1065 -1090
sand brown soft	1102
slate dark soft	1112
lime dark hard	1122
lime dark hard	1200
slate dark soft	1300
lime light hard	1320
shale light rotten	1340
lime light hard	1360
shale blue soft	1380
slate white soft	1400
lime white hard	1415
slate black soft	1435
shale dark soft	1450
lime white hard	1465
shale black soft	1550
lime white hard	1570
shale light soft	1600
lime white soft	1610
shale dark soft	1675
sand white soft	1685
red rock soft	1700
shale black soft	1710
slate white hard	1750
slate black soft	1830
sand white soft	1840
lime white hard	1900
sand white hard	1905
lime white hard	1980
sand brown soft	1985
lime white hard	2095
slate white hard	2110
lime white hard	2115
slate light soft	2125
lime white hard	2160
slate white hard	2217
shale brown soft	2226
lime white hard	2236
sand brown hard	2246

Casing record

"	
15 $\frac{1}{2}$ "	295
12	693
10	1100
8 $\frac{1}{4}$	1754
6 5/8	2226

T. D. Tubing of hole 2245 ft.