

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
 Union National Bk Bldg, Wichita, Kansas.

W. M. MOORE OIL & GAS CO.
 Pixlee No. 4.

SEC. 7 T. 22 R. 10E
 NE & SE 308' fr N&300' fr EL

County. Greenwood

Total Depth. 2338'
 Comm. 1-17-36 Comp. 3-1-36
 Shot or Treated. 60 qts. 2297-2338
 Contractor. Shull Drilling Co.
 Issued. 4-4-36

CASING.

15 1/8" 377'
 12 1/8" 857' UR 925'
 10" 1395'
 8 1/4" 1845' UR 1942'
 6 5/8" 2279' UR 2276'

Elevation.

Production. Est. 200 Bbls.

Figures Indicate Bottom of Formations.

lime light	2	shale sandy	1240
clay white	5	lime	1250
lime light	8	sand	1265
shale grey	70	lime	1280
lime	80	shale	1310
shale	100	sandy lime	1330
lime	110	lime	1405 HFW
shale	120	shale	1410
lime	135	lime	1470
shale	200	shale	1605
lime	205	lime	1620
shale	320	shale	1625
lime	325	lime	1723
shale	375	shale	1728
lime	377	lime	1755
shale	380	shale	1765
lime	385	sandy lime	1780
shale	415	shale sandy	1820
lime	430	shale	1895
shale	445	lime	1900
lime	475	shale	1910
shale	480	GAS SAND	1920 HFW
lime	485	lime	1930
shale	560	shale	1975
lime	565	lime	1995
shale	615	shale	2000
lime	640	lime	2005
shale	660	shale	2015
sandy lime	1 BW 665	lime	2020
shale	690	shale	2030
lime	740	lime	2050
shale	755	shale	2270 SIM 2092
lime	760	reduced hole 2259 cave	
shale	780	sandy shale	2290
lime	800	sand	2338
shale	815	Total Depth	
sand	HFW 850		
shale	855		
lime	867		
shale	885		
lime	895		
shale	915		
lime	925		
shale	930		
lime	940		
shale	980		
lime	990		
shale	1000		
sandy lime	1010		
lime	1030		
shale	1040		
lime	1055		
shale	1092		
sand	1110		
shale	1125		
lime	1200		
shale	1220		