

LOCATION SW NW SW
CASING RECORD


7-22-11E

SEC 7 T 22 R 11E

20" 8 1-4
15 1-2 6 5-8
12 1-2 5 3-16

FARM DeMalorie-Sowder NO. 2
COMPANY Davis-Hazlett et al
CONTRACTOR Davis & Aylard
COMMENCED 2-28-25

COUNTY Greenwood Plotted
L.R.



TOTAL DEPTH QUARTS BETWEEN 2085-2117'

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO

FIGURES INDICATE BOTTOM OF FORMATIONS
DATE ISSUED

ELEVATION
INITIAL PRODUCTION 125 bbls.
16 1/2 hrs.

Formation	Depth	Formation	Depth
mud	15	wtr sand	1175
lime	30	shale	1180
shale	100	lime	1215
lime	120	shale	1220
shale	130	lime	1225
wte. sand	160 5 BW	shale	1230
lime	165	lime	1300
shale	175	shale	1375
lime	185	lime	1380
shale	225	shale	1410
lime	235	lime	1440
shale	260	shale	1445
lime	265	lime	1590
shale	270	shale	1715
lime	280	lime	1720
shale	310	shale	1748
lime	315	lime	1750
shale	330	shale	1785
lime	340	wtr sand	1795
shale	420	1 BW 1790'	
lime	435	lime	1815
shale	495	shale	1920
lime	530	lime	1925
shale	535	shale	1940
lime	540	sand	1950
shale	555	shale	1970
lime	565	shale Top sand	2082
shale	595	U.R. 6" frm 2023-2067'	
lime	610	Oil sand cable	2120
shale	630	SLM	2123 Bottom sand.
lime	640		
shale	645		
lime	665		
shale	685		
lime	695		
shale	725		
lime	730		
shale	790		
lime	795		
shale	815		
lime	840		
shale	865		
lime	875		
shale	905		
lime	910		
shale	1080		
lime	1085		
shale HFW	1105		
wtr sand	1155		
shale	1165		