

WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY
UNION NATIONAL BANK BLDG., WICHITA, KANSAS


27367

CASING RECORD

LOCATION 330' N 330' E E/2 SW/4

SEC 16 T 23 R 11 E.

10" 1015 FARM D. A. Edwards "A" NO. 5 COUNTY Greenwood
20" 8 1/4 1572 COMPANY The Texas Company.
15 1-2 6 5/8 1921 CONTRACTOR Braden-Morrison Drilling Co.
12 1-2 6 19 5 3/16 COMMENCED Jan. 3, 1927. COMPLETED Jan. 25, 1927.



TOTAL DEPTH 1977' SHOT 20 QUARTS BETWEEN 1935-1977'
CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO The Texas Co.,
El Dorado, Kansas.

FIGURES INDICATE BOTTOM OF FORMATIONS.
REMARKS 2/12/27

ELEVATION
INITIAL PRODUCTION

Formation	Depth	Formation	Depth
cellar light	5	shale brown soft	1395
soil light	8	lime white hrd	1400
shale light	23	shale lime	1450
lime white hrd	53	(1445-1450 1 B. W. per hr.)	
slate light soft	63	shale brown soft	1516
lime white hrd	83	shale gray soft	1540
slate blue soft	93	shale white soft	1550
lime white hrd	110	shale blue sandy	1560
slate light soft	154	shale black soft	1572
lime white hrd	166	(Run 6 1/4" 1572')	
shale light soft	242	lime white hrd	1580
lime white hrd	244	lime white hrd	1600
shale light soft	316	shale light soft	1650
lime light soft	340	lime white hrd	1670
lime grey hrd	355	shale brown soft	1680
shale blue soft	405	shale blue soft	1685
lime blue hard	425	lime white hrd	1692
shale white soft	435	shale white soft	1700
lime white hrd	440	lime white hrd	1705
shale blue sandy	450	shale white soft	1750
lime white hrd	455	shale dark soft	1810
shale light soft	475	lime white hrd	1820
lime white hrd	495	shale dark soft	1921
shale white hrd	505	(Set 6 5/8" 1981')	
lime white hard	515	sand oil brown soft	1977
shale white soft	550	SLM Total Depth	1977'
lime white hrd	555		
slate white soft	565		
lime white hrd	570		
slate white soft	615		
shale white soft	619		
(Run 6 1/2" -50# csg.)			
lime white hrd	627		
shale dark soft	632		
lime white hrd	680		
shale white soft	690		
lime white hrd	705		
slate light soft	730		
lime white hrd	735		
slate brown soft	760		
lime white hrd	780		
shale light soft	845		
lime white hrd (HPW at	850		
shale brown soft (865	860		
water sand white soft	885		
lime sandy white sft	900		
lime blue hrd	910		
lime white hrd	935		
shale brown soft	940		
lime white hrd	988		
slate blue soft	996		
lime white hrd	1010		
shale white soft	1015		
(Run 10" at 1015')			
lime white hrd	1055		
shale brown soft	1067		
lime white hrd	1145		
shale white soft	1275		
lime white hrd	1295		
shale white soft	1316		
lime white hard	1390		