

CASING RECORD

LOCATION 330'S 330 E NW $\frac{1}{4}$ SW $\frac{1}{4}$

SEC 16 T 23R 11E.

10" 1017 FARM D.A. Edwards
 20" 8 1-4 1572 COMPANY The Texas Co.
 15 1-2 6 5-8 1900 CONTRACTOR
 12 1-2 566 5 3-16 COMMENCED 11-2-26
 TOTAL DEPTH SHOT

NO. 2B COUNTY Greenwood.

COMPLETED 12-2-26

QUARTS BETWEEN



CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO The Texas Co.

Wichita, Kansas.

ELEVATION

FIGURES INDICATE BOTTOM OF FORMATIONS.

INITIAL PRODUCTION after shot

REMARKS 1-8-27

70 bbls. per Day.

Formation	Depth	Formation	Depth.
cellar	5	shale blue soft	1016
soil	8	lime wh hard	1024
slate grey soft	25	run 1017 of 10" casing.	
lime wh hard	30	shale blue soft	1029
LBW at 25 feet.		lime wh hard	1057
slate white soft	75	shale blue soft	1060
lime wh hard	92	lime wh hard	1140
shale wh soft	160	shale blue soft	1280
lime wh hard	170	lime wh hard	1340
shale grey soft	230	lime grey hard	1355
lime wh hard	240	lime wh hard	1380
shale grey soft	320	shale blk soft	1385
lime wh hard	330	lime wh hard	1415
shale grey soft	335	shale blk soft	1421
lime wh hard	360	lime wh hard	1445
shale grey soft	370	shale light soft	1570
lime hard	385	lime wh hard	1577
shale grey soft	405	run 8- $\frac{1}{4}$ casing 1572	
lime wh hard	423	shale grey soft	1590
shale grey soft	430	lime wh hard	1605
lime wh hard	435	shale brown soft	1637
shale grey soft	445	shale blue	1660
lime wh hard	455	lime wh hard	1685
shale grey soft	472	shale dark soft	1705
lime wh hard	480	lime wh hard	1725
shale grey soft	485	shale blue soft	1818
lime wh hard	490	lime shells dark hard	1838
shale grey soft	495	shale light soft	1900
lime wh hard	500	run 6-5/8 1900	
slate dark soft	551	sand grey hard	1961
Cave.		T.D.	1961
lime wh hard	570		
run 566 of 12 $\frac{1}{2}$ casing			
slate wh soft	585		
shale brown soft	615		
lime wh hard	623		
shale dark soft	635		
lime wh hard	675		
shale dark soft	683		
lime wh hard	710		
slate wh soft	740		
shale brown soft	787		
slate brown soft	840		
lime wh hard	852		
shale grey soft	863		
sand water grey soft	915		
HPW 863--915			
shale brown soft	936		
lime wh hard	940		
shale brown soft	950		
lime wh hard	984		