

WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY
UNION NATIONAL BANK BLDG., WICHITA, KANSAS

27345

CASING RECORD

LOCATION NE c SW SW

SEC 16 T 23 R 11E

10" 960 FARM E. A. Edwards NO. 1 COUNTY Greenwood
20" 8 1-4 1350 COMPANY The Texas Company
15 1-2 6 5-8 1897 CONTRACTOR George Hinkle
12 1-2 535 5 3-16 COMMENCED Oct-25-26
TOTAL DEPTH 1969 SHOT 180 QUARTS BETWEEN 1966-1969'



CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO Texas Company

El Dorado, Kansas.

FIGURES INDICATE BOTTOM OF FORMATIONS.

REMARKS 4/9/27.

ELEVATION
INITIAL PRODUCTION 167½ bbls.

Formation	Depth	Formation	Depth
soil yelooow hard	2	slate blue soft	990
lime white hard	10	big lime white hrd	1020
shale grey soft	12	lime white hrd	1040
lime white hard	40	shale blue soft	1045
shale grey soft	50	lime white hard	1137
lime white hard	70	shale blue soft	1252
shale grey soft	90	lime white hard	1365
lime white hard	98	shale blue soft	1374
shale grey soft	120	lime white hard	1395
shale blue soft	150	shale blue soft	1400
lime white hard	165	lime white hard	1420
shale blue soft	200	shale blue soft	1425
lime white hard	230	lime white hard	1435
shale blue soft	240	shale blue soft	1530
lime white hard	250	lime white hard	1535
slate blue soft	280	shale blue soft	1545
lime white hard	345	lime white hard	1550
shale blue soft	365	lime white hard	1565
lime white hard	385	shale blue soft	1570
shale blue soft	400	lime white hard	1590
lime white hard	405	shale blue soft	1625
shale blue soft	415	lime white hard	1640
lime white hard	438	shale blue soft	1655
shale blue soft	445	lime white hrd	1663
lime white hard	465	shale blue soft	1680
shale blue soft	470	lime white hrd	1686
lime white hrd	510	lime white hrd	1700
shale blue soft	535	shale blue soft	1780
(Run 12½" at 535')		lime white hrd	1788
lime white hard	555	shale blue sft	1792
shale blue soft	575	lime white hrd	1800
lime white hard	585	shale blue sft	1895
shale blue soft	600	lime white hrd Show of oil	1897
shale grey soft	610	sand brown soft	1900
lime white hard	625	sand brown soft	1966
lime white hrd	662	Best pay 1900-1925'	
shale grey soft	680	shale blue white	1969
lime white hrd	705	S. L. M. T. D.	1969'.
shale grey soft	710		
lime white hrd	730	Filled up 1000' white drilling in.	
slate grey medium	750		
lime white hrd	765		
shale blue soft	820		
lime white hrd	835		
shale blue sft	845		
(5' sand carried water)			
lime white hard	885		
shale blue soft	890		
sand white soft HFW 880-895'	895		
lime white hard	910		
sand white hrd	920		
shale grey soft	955		
lime white hrd	965		
sand white sft HFW at 965'	975		
sandy shale grey soft	985		
(Run 10" at 960')			