


Location NE NW SE

Sec.19 T. 23 R.10E

Casing Record

County- Greenwood

20" 10" 1208 Farm- A. C. Race No. 3  
 15 1/2" 8 1/2" " Company- Independent Oil and Gas Co. (Mission)  
 12 1/2" 382 53/16" 1962 Contr.- Roth-Faurot  
 Comm.- 4/23/29 Comp.- 6/1/29



Total Depth 2315' Shot 20 Quarts Between  
 Correspondence Regarding This Well Should Be Referred to Roth-Faurot  
 Independence, Kansas Elevation

Figures Indicate Bottom of Formations. Initial Production Dry  
 Date Issued. 7/13/29

Formation	Depth	Formation	Depth
broken lime	15	lime white hard	1065
shale blue	60	shale gray soft	1150
lime	65	shale light soft	1198
shale blue	80	lime gray hard	1212
shale white	94	shale blue soft	1215
red rock	97	water sand gray	1255
shale	175	shale gray	1260
red rock	195	lime broken soft	1270
shale white	205	lime white hard	1275
lime white	210	water sand	1340
shale gray	280	lime white hard	1345
lime shell white	283	lime gray soft	1375
shale gray	383	lime white hard	1511
lime white	397	shale blue soft	1540
shale gray	420	lime gray hard	1610
shale white	485	shale blue soft	1620
lime gray	495	lime white hard	1785 Oswego
shale gray	525	shale dark soft	1845
lime white	540	lime gray hard	1905
slate gray	580	shale blue soft	1930
lime white	595	lime white hard	1940
slate gray	655	shale white soft	1975
lime gray	660	lime white hard	2005
shale gray	670	shale light soft	2185
lime white	685	shale dark soft	2262
shale white	695	sand dark soft	2272
lime	735	sand lime dark	2279
shale gray	760	Oil show 2 B in	
lime white hrd	765	26 hours.	
shale blue sft	770	shale dark soft	2289
lime shell white sft	773	sandy lime soft	2294
shale white sft	780	shale dark soft	2315 T.D.
lime white hrd	785		
shale white sft	800	Plugged back to	2282'
lime gray	815	Abandoned	
shale blue	830	Finished pulling pipe and	
lime gray	840	plugging June 14, 1929.	
shale blue	855	Lost 9 1/2 Joints 5-3/16"	
lime white hrd	875	Pipe in Hole.	
shale white sft	880		
lime white hard	895		
shale white soft	910		
shale blue soft	960		
lime gray hard	970		
shale blue soft	980		
lime white hard	1030		
shale dark soft	1045		