

Location NW cor W/2 SE/4


Sec. 21 T. 23 R. 11E.

Casing Record

County- Greenwood.

10" Farm- D. A. Edwards No. 2-C.
 20" 8" Company- Texas Co.
 15 1/8" 65/8" Contr.-
 12 3/8" 53/16" Conn.- 1/23/29. Comp.- 3/7/29.

Total Depth 1974'. Shot Quarts Between
 Correspondence Regarding This Well Should Be Referred to



Figures Indicate Bottom of Formations. Elevation
 Date Issued. 3/16/1929. Initial Production
 Est. 452 bbls.

Formation	Depth	Formation	Depth.
lime	5	lime white hard	1010
shale blue	10	shale blue soft HFW	1015
lime white	25	10" 1024	
shale grey	30	lime white hard	1065
lime white	50	shale blue soft	1070
mud blue	55	lime white hard	1120
lime white hard	60	shale blue soft	1230
shale dark	90	lime white hard	1360
lime white	100	sand soft white 5BWP	1368
shale blue soft	190	lime white hard	1395
lime white hard	225	shale light soft	1400
shale grey	260	lime white hard 5BWP	1405
lime white hard	315	shale blue soft cave	1530
shale dark	325	lime wh hard	1531
lime white	335	lime white soft 8 1/2	1521 1543
shale grey	365	lime white hard	1552
lime white	385	shale white soft	1605
shale blue soft	395	lime white hard	1615
lime white hard	410	shale light soft	1630
lime grey	422	lime grey	1645
shale grey soft	430	slate blk soft	1650
lime white hard	440	lime grey hard	1655
shale blue soft	460	shale light soft	1665
lime grey hard	470	lime hard	1670
shale grey	505	shale light soft	1800
lime grey hard	530	shale dark	1850
shale grey	560	shale grey	1868
lime white shells	563	sand dark	1876
shale grey	580	6" 1870	
lime grey hard	590	sand (oil) S.L.M.	1971
shale blue soft	600	shale dark	1974TD.
571' 12 1/2 pipe.			
lime grey hard	640		
shale white	645		
lime white hard	655		
shale grey	665		
lime grey hard	670		
shale blue soft	675		
lime grey hard	685		
shale blue soft	750		
lime white hard	760		
shale grey sdy	830		
lime wh hard	835		
sand white	880		
shale sdy	895		
lime grey hard	900		
shale blue soft	910		
lime grey hard	965		
slate	970		