

UNION NATIONAL BANK BLDG., WICHITA, KANSAS.

Location ~~SW~~ NW SE

Sec. 21 T. 23 R. 11E

990' fr NL, 330' fr EL W $\frac{1}{2}$ SW $\frac{1}{4}$

Casing Record

County - Greenwood
No. 5 - C.

20" 10" 1002
15 $\frac{1}{2}$ " 8 $\frac{1}{2}$ " 1620
12 $\frac{1}{2}$ " 65/8" 1871
12 $\frac{1}{2}$ " 561 53/16"

Farm - D. A. Edwards
Company - The Texas Company
Contr. - G. W. Hinkle
Comm. - 6/16/29

Comp. - 7/9/29

Total Depth 1963

Shot 260 Quarts Between 1894-1962

Correspondence Regarding This Well Should Be Referred to



Elevation

Figures Indicate Bottom of Formations.

Initial Production 210 Bbls
1st 12 hrs.

Date Issued. 7/20/29

Formation	Depth	Formation	Depth
soil	10	slate blue soft	995
slate blue soft	105	lime gray hard	1002
slate white soft	120	lime white hard	1080
slate blue soft	175	2 BW per hr.	
lime gray hard	195	shale blue soft	1090
slate blue soft	215	shale white soft	1170
slate blue soft	257	shale blue soft	1210
lime gray hard HFW	270	lime gray hard	1228
slate white	285	shale blue soft	1232
lime white hard	317	slate white soft	1250
slate blue soft	319	lime white hard	1275
1 BW pr. hr. 319-325'		lime gray hard	1315
lime white hard	325	lime white hard	1355
slate blue soft	350	lime gray hard	1387
lime white hard	365	shale blue soft	1395
slate blue soft	370	slate blue soft	1485
lime gray hard	389	slate blue soft	1490
slate blue soft	395	lime gray hard	1511
lime gray hard	400	shale blue soft	1535
slate blue soft	405	Cave	
slate white soft	410	lime white hard	1555
lime gray hard	420	slate blue soft	1580
slate white soft	425	shale blue soft	1595
lime gray hard	429	lime gray hard	1600
slate blue soft	434	shale blue soft	1618
lime gray hard	445	lime gray hard	1628
lime white hard	450	slate blue soft	1633
slate blue soft	485	lime gray hard	1637
lime white hard	500	shale blue soft	1690
lime gray hard	508	shale white soft	1740
slate blue soft	530	shale brown soft	1755
lime gray hard	535	shale white soft	1760
slate blue soft	555	shale white soft	1790
lime white hard	571	shale black soft	1810
slate blue soft	583	shale white soft	1835
lime white harder	610	shale black soft	1855
lime white hard	620	shale white soft	1864
slate blue soft	625	slate black soft	1870
slate white soft	650	lime white hard	1871
slate blue soft	670	sand brown med. OIL	1963
slate white soft	685		
slate blue soft	694	Total Depth SLM	1963'
lime gray hard	700		
slate blue soft	765		
slate blue soft HFW	830		
sand white med. HFW	865		
shale blue soft	945		
lime white hard	980		
shale blue soft	985		
lime white hard	990		