

THICKNESS	FORMATIONS	TOTAL DEPTH
1	Soil	1
14	Clay	15
13	Lime	28
3	Black Shale	31
4	Shale Light	35
3	Lime	38
12	Shale	50
10	Shale/Lime Streaks	60
21	Shale	81
2	Lime Dark	83
10	Shale/Lime Streaks	93
22	Shale Dark	115
19	Shale Light	134
1	Lime	135
6	Black Shale	141
30	Shale Light	171
1	Black Shale	172
2	Shale	174
1	Lime	175
1	Shale Light	176
21	Black Shale	197
5	Light Shale	202
19	Sandy Shale	221
14	Sandy Shale	235
10	Oil Sand	245
7	Sandy Shale	252
38	Shale Light	290
19	Shale	309
8	Sand Dry	317
10	Shale	327
3	Sandy	330
3	Shale	333

RECEIVED
 STATE CORPORATION COMMISSION
 APR 19 1900
 CONSERVATION DIVISION
 Wichita, Kansas

T. D. 333

Set 166ft. of 9" Dry Pipe
 Core from 202 to 221
 Cored from 221 to 240
 Cored from 240 to 252
 Cored from 290 to 309
 Cored from 309 to 327

Report of all strings set — surface, intermediate, production, etc. CASING RECORD ((New)) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 1/4"	9"		60	Consolidated Quick Set	35	None
Production	8 3/4	4 1/2		260	Consolidated Quick Set	45	None

LINER RECORD			PERFORATION RECORD		
Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
			4	HSC 3/8	240 - 245

TUBING RECORD	
Setting depth	Pecker set at