

WELL LOG BUREAU KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas


Company - SAM PACK ETAL
Farm - Witt

No. 1

SEC. 29 T. 23 R. 4E
NE NW SW

Total Depth. 2421
Comm. 11-2-49 Comp. 12-3-49
Shot or Treated.
Contractor. A. D. Allison & Co.
Issued. 12-24-49

County. Butler
KANSAS



Elevation. 1357 *ft.*

Production. dry

CASING:

15 1/2" 68' 10" 1676'
12 1/2" 855' 7" 2225'

Figures Indicate Bottom of Formations.

soil	5	shale	1055	12-3-49, drilled deeper
shale HFV 35-40	25	lime	1065	lime 2421
gravel & water sand	40	shale	1115	HFV, no increase in oil
shale, shells	60	lime	1165	Total Depth 2421
shale	70	shale	1180	
lime soft	100	lime	1210	Well abandoned
shale	120	shale	1215	
lime	165	lime	1225	
shale	175	shale	1230	
shale shells	225	lime	1270	
lime	250	shale	1275	
shale	265	lime	1295	
lime	275	shale	1310	
shale	280	lime	1370	
lime	290	shale	1405	
shale	300	lime	1455	
lime	310	shale	1460	
shale	315	lime	1480	
lime	325	shale	1495	
shale	330	lime	1500	
lime	350	shale	1535	
shale	355	sand 2B" 35-40	1540	
lime	390	shale	1620	
shale	405	lime	1625	
red rock	415	shale	1660	
lime	420	lime	1672	
shale	423	shale	1725	
lime	430	lime	1750	
shale	440	shale	1755	
lime	500	lime	1760	
shale	505	shale	1765	
lime	530	lime	1835	
shale	545	shale	1985	
lime	555	lime	2015	
shale 1B" 50-55	560	shale	2020	
lime	570	lime	2040	
shale	600	shale	2045	
red rock	605	lime	2084	
lime	610	shale blk	2089	
shale	635	lime	2118	
lime	650	shale	2123	
shale	685	lime	2145	
lime	690	shale	2200	
shale, shells	735	lime	2215	
shale	770	shale	2230	
lime 1B" 780	785	lime	2255	
shale	820	shale	2260	
lime	835	lime	2290	
shale	840	lime cherty	2295	
lime	850	chat, Show Oil 2320-25		
shale, shells	875		2325	
lime	910	red rock	2330	
shale	915	shale	2415	
lime	925	lime Show oil 2416	2418	
shale, shells	970	8 gal oil pr hr	2417	
lime 2B" 970-75	980	12-2-49, testing well		
shale	1010	3 1/2 gal oil 45 gal water pr hr.		
lime	1035			