

# WELL RECORD and LOG

Well No. 8.

Frank

Far

Location \_\_\_\_\_ Sec. \_\_\_\_\_ Twp. \_\_\_\_\_ Rge. \_\_\_\_\_ County \_\_\_\_\_

Rig Commenced	19	} Contractor	This Well Was Drilled With  Rotary or Cable Tools } <u>Cable Tools</u>
Rig Completed	19		
Drilling Commenced	<u>4/20</u> 19 <u>20</u>	} <u>Rosenthal + Beardmore</u> Contractor	Finished with Tools or Star Machine } _____
Drilling Completed	<u>6/10</u> 19 <u>20</u>		

## CASING and TUBING

PUT IN WELL		PULLED OUT OF WELL		LEFT IN WELL		REMARKS
FEET	INCHES	FEET	INCHES	FEET	INCHES	
<u>15 1/2</u> 70 <sup>#</sup>	118 8	60		58 8		<u>Tape Line Measurement</u>
<u>1 1/2</u> 50 <sup>#</sup>	900	900				
<u>40</u> 2 <sup>#</sup>	1398	1398				
<u>28</u> 2 <sup>#</sup>	2147			2147		<u>Steel Line Measurement</u>
<u>18</u> 20 <sup>#</sup>	2468			2468		

Well abandoned Nov. 11, 1921  
**SAND RECORD**

NAME	TOP	BOTTOM	FEET OF SAND	REMARKS
	2468	2469		

Shot \_\_\_\_\_ 19 \_\_\_\_\_ By \_\_\_\_\_ Shooter \_\_\_\_\_

Size of Shot \_\_\_\_\_ Sand Shot \_\_\_\_\_

Production First 24 Hours 300 bbls. Gravity \_\_\_\_\_

## DRILLING BILL

June 24 1921

To White Eagle Oil Refg Co Dr.

To Drilling	<u>2468</u> Feet at \$ <u>3.50</u>	Per Foot \$ <u>86.38</u> <sup>00</sup>	
To Underreaming	<u>Day Work</u> Tours at \$ _____	Per Tour \$ <u>545</u>	
To Pulling Pipe	Tours at \$ _____	Per Tour \$ _____	
<b>TOTAL \$</b>		<u>91.83</u>	

*NAVR 1111*

FROM	TO	FEE	FORMATION	FROM	TO	FEE	FORMATION
0	15		Soil	1770	1800		Lime
15	65		Lime	1800	1825		Slate
65	70		Slate	1825	2120		Lime
70	75		Lime	2120	2135		Sand Hole full Water <sup>2</sup>
75	80		Red Rock	2135	2240		Lime Run 2145' 8" Casing
80	120		Lime	2240	2270		Slate
120	140		Slate Casing } 11 8' 8" 15 1/2'	2270	2285		Lime
140	240		Lime	2285	2360		Slate
240	275		Lime	2360	2375		Lime
275	290		Slate	2375	2400		Slate
290	295		Red Rock	2400	2410		Red Rock
295	400		Lime	2410	2420		Shale
400	425		Slate	2420	2468		Slate (top of Sand Run 2468' 6 1/8" Casing)
425	480		Lime				
480	510		Slate				
510	515		Sand 1 Barrel Water				
515	580		Slate				
580	665		Lime				
665	730		Slate				
730	750		Lime				
750	785		Slate				
785	795		Lime				
795	800		Slate				
800	870		Lime Run 900ft 12 1/2"				
870	920		Slate Casing				
920	930		Slate				
930	980		Lime				
980	990		Slate				
990	1010		Lime				
1010	1070		Slate				
1070	1030		Lime				
1030	1050		Slate				
1050	1170		Lime				
1170	1110		Slate				
1110	1160		Lime				
1160	1190		Slate				
1190	1210		Sand 5 Barrels Water				
1210	1380		Lime Run 1398' 10" Casing				
1380	1390		Slate				
1390	1410		Lime				
1410	1420		Slate				
1420	1485		Lime				
1485	1515		Slate				
1515	1585		Lime				
1585	1600		Lime				
1600	1770		Slate				

Note: - This Well plugged and Abandoned on Nov. 14th, 1921.