


Greenwood 5-23-11E

10" 1000 FARM Seeley  
 20" 8 1-4 1638 COMPANY Vickers & Johnson  
 15 1-2 6 5-8 1920 CONTRACTOR  
 12 1-2 610 5 3-16 COMMENCED July 30, 1923

NO. 2 COUNTY



TOTAL DEPTH 1963' SHOT 120 QUARTS BETWEEN 1924-1956

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO Vickers & Johnson, Wichita, Kansas.

ELEVATION 1st 24 hr. 100

FIGURES INDICATE BOTTOM OF FORMATIONS

INITIAL PRODUCTION

REMARKS

bbis.

| Formation                      | Depth | Formation                       | Depth     |
|--------------------------------|-------|---------------------------------|-----------|
| surface                        | 5     | lime                            | 1658      |
| blue mud ( 2 B.W. at 20')      | 30    | slate-                          | 1665      |
| lime                           | 40    | shale                           | 1670      |
| lime                           | 50    | lime                            | 1675      |
| shale                          | 65    | shale                           | 1685      |
| lime                           | 90    | lime                            | 1695      |
| blue mud                       | 155   | shale                           | 1700      |
| lime                           | 160   | lime                            | 1710      |
| slate                          | 200   | shale                           | 1720      |
| shale                          | 240   | slate                           | 1755      |
| lime                           | 260   | lime                            | 1765      |
| shale                          | 265   | slate                           | 1806      |
| shale                          | 310   | lime                            | 1812      |
| lime                           | 360   | shale                           | 1891      |
| shale                          | 385   | slate                           | 1920      |
| lime                           | 400   | sand                            | 1934      |
| shale                          | 445   | (1st show oil at 1925)          |           |
| sandy lime                     | 475   | coarse brown sand               | 1939      |
| lime                           | 485   | ( filled up to 400' from        |           |
| shale                          | 555   | 1934-1939')                     |           |
| lime                           | 565   | brown sand ( filled up to 500') | 1943      |
| shale                          | 610   | ( with oil from 1939)           |           |
| lime                           | 670   | ( to 1943)                      |           |
| slate                          | 675   | brown sand                      | 1949      |
| lime                           | 695   | (filled up to 600' from 1943)   |           |
| slate                          | 720   | (to 1949)                       |           |
| lime                           | 725   | brown sand                      | 1954      |
| slate                          | 765   | (filled up to 700' from         |           |
| shale                          | 830   | 1949 -1954)                     |           |
| lime                           | 835   | brown sand                      | 1959      |
| shale                          | 855   | brown sand                      | 1963T. D. |
| water sand ( B.P.W. at 865')   | 990   |                                 |           |
| slate                          | 1011  |                                 |           |
| lime (B.P.W. 1000-1020)        | 1020  |                                 |           |
| hard lime                      | 1030  |                                 |           |
| lime                           | 1110  |                                 |           |
| soft lime (1 1/2 B.W. per hr   | 1120  |                                 |           |
| 1 line at 1120')               | 1150  |                                 |           |
| shale                          | 1230  |                                 |           |
| lime                           | 1310  |                                 |           |
| shale                          | 1315  |                                 |           |
| lime hard                      | 1345  |                                 |           |
| lime ( 3 B.W. per hr at 1380') | 1400  |                                 |           |
| lime                           | 1400  |                                 |           |
| shale                          | 1570  |                                 |           |
| slate                          | 1575  |                                 |           |
| lime                           | 1590  |                                 |           |
| shale                          | 1590  |                                 |           |
| lime                           | 1605  |                                 |           |
| sand ( 4 B.W. /hr at 1610')    | 1615  |                                 |           |

X 1000' of fluid in hole after shutting down 12 hrs.

sand ( 5 B.W./hr at 1610-1625')  
 shale 1635  
 slate 1650