

WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY
BITTING BUILDING, WICHITA, KANSAS

CASING RECORD

LOCATION ~~NE~~ ^{NE-NE-NW} 330' from N.L. & ~~EE~~ 33' from E. L.

SEC 5 T 23 R 11 E.

10" 1004 FARM R. P. Seeley NO. 7 COUNTY Greenwood

20" 8 1-4 1666 COMPANY White Eagle Oil & Refining Co.

15 1-2 6 5-8 1926 CONTRACTOR

12 1-2 572 5 3-16 COMMENCED Feb. 25, 1923 COMPLETED March 18, 1923.



TOTAL DEPTH 1987 $\frac{1}{2}$ '

SHOT 120 QUARTS BETWEEN

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO

FIGURES INDICATE BOTTOM OF FORMATIONS

ELEVATION
INITIAL PRODUCTION

REMARKS

Formation	Depth	Formation	Depth
soil	15	slate	1575
slate	45	lime	1605
lime	50	slate	1610
slate	100	sand	1625
lime	115	slate	1645
slate	150	lime	1650
lime	160	slate	1665
slate	165	lime	1668
	175	shale	1678
lime	190	lime	1682
slate	240	shale	1693
lime	250	lime	1700
slate	260	lime	1730
lime	270	lime	1740
slate	335	slate	1755
lime	350	lime	1770
slate	365	slate	1775
lime	375	lime	1800
slate	425	slate	1835
lime	440	slate	1902
slate	450	sandy shale	1914
lime	455	dark shale	1918
slate	465	sandy shale	1949
lime	475	Oil sand	1987 $\frac{1}{2}$ T. D.
slate	490		
slate	520		
lime	535		
slate	560		
lime	570		
slate	620		
lime	630		
slate	650		
lime	685		
slate	695		
lime	715		
slate	865		
sand (H.F. W. at 870)	963		
slate	975		
sand	988		
slate	1006		
lime	1015		
lime (1 B.W. at 1115)	1120		
lime	1150		
slate	1160		
lime	1167		
slate	1280		
lime	1295		
slate	1300		
lime	1350		
sand	1365		
lime (3 B.W. at 1390)	1395		
sand	1405		
lime	1440		
slate	1500		

Gift of
 W. L. Stryker Estate
 State Geological Survey of Kansas
 1970

E $\frac{1}{2}$ of NW $\frac{1}{4}$ 5 - 23 - 11

NE-NE-NW

R. P. Seeley Well No. 7.
 Greenwood County, Kansas

Shot 120
 qts.

soil	15
slate	45
lime	50
slate	100
lime	115
slate	150
lime	160
slate	165
	175
lime	190
slate	240
lime	250
slate	260
lime	270
slate	335
lime	350
slate	365
lime	375
slate	425
lime	440
slate	450
lime	455
slate	465
lime	475
slate	490
slate	520
lime	535
slate	560
lime	570
slate	620
lime	630
slate	650
lime	685
slate	695
lime	715
slate	865
sand HFW @ 870'	963
slate	975
sand	988
slate	1006
lime 1 B.W. @ 1115'	1120
lime	1150
slate	1160
lime	1167
slate	1280
lime	1295
slate	1300
lime	1350
sand	1365
lime 3 BW @ 1390'	1395
sand	1405
slate	1575
lime	1605
slate	1610
sand	1625
slate	1645
lime	1650

White Eagle Oil & Refg. Co.

Drilling commenced 2-25-23
 Drilling completed 3-18-23

Casing Record:

12 $\frac{1}{2}$ "	572'
10"	1004'
8 $\frac{1}{4}$ "	1666'
6 5/8"	1926'

330' from N. line of $\frac{1}{4}$ Sec.
 330' from E. line of $\frac{1}{4}$ Sec.

slate	1665
lime	1668
shale	1678
lime	1682
shale	1693
lime	1740
slate	1755
lime	1770
slate	1775
lime	1880
slate	1902
sandy shale	1914
dark shale	1918
sandy shale	1949
oil sand	1987