

WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY  
 UNION NATIONAL BANK BLDG., WICHITA, KANSAS


CASING RECORD

LOCATION NEcSW<sup>1</sup>/<sub>4</sub>

SEC 8 T 23 R 10E.

10"  
 20" 8 1-4  
 15 1-2 6 5-8  
 12 1-2 5 3-16

FARM Culver NO. 1 COUNTY Greenwood.  
 COMPANY Leonard Petroleum Co.  
 CONTRACTOR  
 COMMENCED Jan 5, 1927 COMPLETED Feb 16, 1927  
 SHOT QUARTS BETWEEN



TOTAL DEPTH  
 CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO

ELEVATION  
 INITIAL PRODUCTION

FIGURES INDICATE BOTTOM OF FORMATIONS.  
 REMARKS 4-9-27

Formattion	Depth	Formation	Depth.
soil soft	9	lime hard	1100
lime white firm	15	slate soft	1135
slate blue soft	33	lime firm	1140
lime hard	41	slate soft 1 <sup>1</sup> / <sub>2</sub> BW	1230-40 1230
slate white soft	60	sdv shale	1245
slate soft LBW 80-85	80	slate soft	1275
gritty lime hard	85	lime firm	1290
slate blue soft	240	slate soft	1320
red slate soft	244	sand grey soft	1342
slate soft	315	HFW 1320-42	
firm lime	325	slate	1345
slate soft	375	sand grey soft	1352
lime hard	378	slate soft	1369
slate soft	460	sand grey soft	1390
lime hard	470	slate blue soft	1396
slate soft	495	sand dark soft	1426
lime hard	500	lime hard	1432
slate soft	503	slate blue soft	1452
lime firm	507	sand soft	1460
slate soft	520	lime firm	1575
lime broken firm	531	slate soft	1680
slate soft	546	lime hard	1683
lime hard	554	slate soft	1700
slate soft	557	lime hard	1835
hard lime	562	sand soft 2BWPBR	1845 1845
slate	600	slate soft	1855
lime firm	603	lime soft hard	1870
slate soft	635	slate soft	1873
brown hard lime	643	lime hard	1881
slate soft	690	slate soft	2050
hard lime	700	sand grey soft	2057
slate soft	706	4BW 2057	
lime hard	715	slate soft	2090
slate soft	755	lime hard	2100
lime firm	770	slate soft	2120
slate soft	795	lime broken med	2140
lime firm	800	slate soft	2145
slate soft	810	lime broken soft	2170
lime hard	820	sdv shale soft	2180
slate soft	837	slate soft	2260
lime hard	841	lime brown hard	2263
slate soft	872	slate soft	2295
hard lime	878	sdv shale soft	2340
soft slate	891	slate dark soft	2345
hard lime	897	sdv shale light sft	2355
sdv lime LBW 905 5BW 911	905	sand light soft	2367
hard lime	911	slate blue soft	2401
slate	925	sdv shale light soft	2425
lime firm	935	slate blue soft	2470
slate soft	950	Miss lime firm	2487
		5 bailers of water per hr at top of lime	
lime firm	955	T.D.	2487 feet
slate soft	1000		
lime hard	1008		
slate soft	1011		
lime hard	1017		
soft slate	1055		
lime hard	1061		
slate soft	1080		