

CENTRAL PETROLEUM CORP.
Bratton No. 6

SEC. 14 T. 24 R. 9E.
NW NE NW NE
220' fr NL 530' fr EL.
NW/4 of NE/4

Total Depth. 2166 P.B. 2153.
Comm. 12-6-36 Comp. 1-5-37
Shot or Treated. 60 qts 2129-2153
Contractor. Harry Gore.
Issued. 1-30-37

County Greenwood.

CASING.

12 $\frac{1}{2}$ " 33'
10" 1123'
8 $\frac{1}{4}$ " 1329'
65/8" 1770'
53/16" 2109'

Elevation.

Production. 40 B.

Figures Indicate Bottom of Formations.

soil soft	5	lime	760
gravel hard	10	shale	765
shale soft	25	lime	800
lime hard	30	shale	805
shale	105	lime	830
lime	115	shale	845
shale	135	lime	860
lime	145	shale	925
shale	150	sand shale	940
lime	160	slate shells	1020
shale	170	lime	1025
lime	175	water sand	1120
slate	215	lime	1125
lime	225	slate	1135
shale	235	sand	1155
lime	265	shale	1175
shale	270	lime Big	1322
lime	280	shale	1460
shale	305	lime	1470
lime	310	shale	1475
shale	325	Oswego lime	1565
lime	330	shale	1575
shale	350	lime	1605
lime	370	shale	1735
shale	375	lime	1740
slate	380	shale	1767
lime	405	lime	1775
shale	420	shale	1780
lime	440	lime	1790
shale	490	shale	1825
lime	510	lime	1840
shale	520	shale	1855
lime	535	lime	1865
shale	550	shale	1885
lime	560	lime	1900
shale	585	shale	1940
lime	590	lime	1950
shale	595	shale	1980
lime	635	lime	1990
shale	645	shale	2000
lime	655	lime	2010
shale	675	slate and shells	2107
lime	690	sand	2153
shale	715	shale	2163
lime	730	Water sand	2166
shale and shells	750	Total Depth.	

$\frac{1}{2}$ BW 640' P.B. 2153.
HFW 1025 Oswego lime 1475-1565
HFW 1135-1155 show oil 1590-1600
 $\frac{1}{2}$ BW 1525-1530 Bartlesville sd 2107
2 BW 1590-1600 -2153
Oil 2130-2152