


Well Log Bureau, KS Geo Soc.

Total Depth, 2239
Comm. 5-3-40 Comp. 7-21-40
Shot or Treated, 140 qts.
Contractor,
Issued, 8-10-40

County Greenwood.



CASING.

10"	950'	Pulled,	Elevation,
8 $\frac{1}{2}$ "	1440'	Left in	
6 $\frac{5}{8}$ "	2183'	Left in	Production, 50 B.

Figures Indicate Bottom of Formations. after shot.

lime	20	lime	715	shale	2005
shale	30	lime	730	lime	2025
lime	50	shale	735	shale	2100
shale	90	lime	755	lime	2110
lime	100	shale	785	shale	2187
shale	110	lime	800	oil sand	2228
lime	120	shale	835	shale blk	2232
shale	130	lime	840	Pay 2193-2228 shot 140 qts.	
lime	140	shale	860	Filled 135' Oil overnight.	
shale	190	lime	870	shale	2239
broken lime	200	shale	895		
shale	215	lime	910	Total Depth.	
lime	220	shale	915		
broken lime	230	lime	960		
shale	245	sdv lime	970		
lime	255	shale	980		
shale	260	lime	985		
lime	275	shale	1020		
shale	290	sand	1045		
lime	310	water	1020-45		
shale	320	shale	1155		
lime	330	lime	1165		
shale	335	water sand	1175		
lime	355	sdv shale	1190		
shale	400	shale	1225		
lime	408	sdv lime	1255		
shale	435	lime	1270		
lime	460	shale	1285		
shale	485	lime	1350		
shale & shells	505	sdv lime	1365		
shale	510	HFW	1350-65		
lime	515	lime	1437		
shale	525	shale	1570		
lime	530	lime	1675		
shale	570	1 $\frac{1}{2}$ BWPFR	1650-60		
lime	600	shale blk	1680		
shale	615	lime	1735		
lime	625	shale	1850		
shale	640	lime	1855		
lime	645	shale	1870		
shale	670	lime	1890		
lime	690	shale	1950		
shale	695	lime	1960		
lime	700	shale	1985		
shale	710	lime	2000		