

**WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY
UNION NATIONAL BANK BLDG., WICHITA, KANSAS**

CASING RECORD

LOCATION 330' fr SL 330' fr EL E/2 SE/4 SEC 25 T 24 R 10E

10" 1070 FARM F. T. Nixon NO. 4 COUNTY Greenwood
20" 8 1-4 1561 COMPANY Phillips Petroleum Co.
15 1-2 6 5-8 1820 CONTRACTOR
12 1-2 580 5 3-16 COMMENCED 8/23/26. COMPLETED 9/13/26.

TOTAL DEPTH 1848 SHOT 75 QUARTS BETWEEN 1830-1847

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO Phillips Petroleum Co.,
Bartlesville, Oklahoma. ELEVATION

FIGURES INDICATE BOTTOM OF FORMATIONS.

INITIAL PRODUCTION 75 bbls.

REMARKS 10/16/26.

SAND RECORD

Top of sand 1819 top first oil 1834 bottom oil sand 1847 total depth 1895½ plugged back 1848 present total depth 1848. Sand gray soft. Shale from 1848-1879 dry sand to 1891 blue shale to 1895½. Plugged back to 1848'.

Formation	Depth	Formation	Depth
surface light soft	10	lime white hrd	700
lime white hrd	20	shale dark soft	710
shale dark soft	30	lime white hrd	740
lime white hrd	45	shale dark soft	830
shale dark soft	100	lime white hrd	835
lime white hrd	105	shale light soft	865
shale dark soft	175	sand light hrd (HFW 875')	895
lime white hrd	185	sand soft	965
shale light soft	200	lime white hrd	1110
shale dark soft	280	shale dark soft	1265
lime white hrd	290	(10" 1065')	
shale dark soft	320	lime white hrd	1285
lime white hrd	330	shale light soft	1305
shale dark soft	350	(12 B. W. at 1105')	
shale gray soft	430	lime white hrd	1425
lime white hrd	450	shale light soft	1560
shale dark soft	495	(8" 1566')	
lime white hrd	505	lime white hrd	1570
shale light soft (2 BW 565')	550	shale dark soft	1585
lime white hrd	560	lime white hrd	1605
shale dark soft	570	shale light soft	1630
lime white hrd (12½" at 580')	585	shale light soft	1750
shale gray sft	595	shale light soft	1829
lime white hrd	610	(6 5/8" at 1814 SL correction 1819')	
shale drk sft	625	sand gray sft	1848
lime white hrd	660	shale black	1879
shale lgt sft	680	sand dry	1891
		shale blue	1895½
		plugged back to	1848
		Total Depth	1848½