



OILFIELD RESEARCH LABORATORIES

536 NORTH HIGHLAND - CHANUTE, KANSAS - PHONE HE1-2650

July 19, 1966

Jackson Brothers
514 North Main
Eureka, Kansas

Gentlemen:

Enclosed herewith is the report of the analysis of the Rotary core taken from the Perrier Lease, Well No. 6, Greenwood County, Kansas, and submitted to our laboratory on July 13, 1966.

Your business is greatly appreciated.

Very truly yours,

OILFIELD RESEARCH LABORATORIES

Carl L. Pate

CLP:rf

6 c.

Oilfield Research Laboratories

GENERAL INFORMATION & SUMMARY

Company Jackson Bros. Lease Perrier Well No. 6

Location NE NW SE

Section 17¹⁶ Twp. 25S Rge. 8E 9E County Greenwood State Kansas

| | |
|--------------------------------|--------------|
| Name of Sand | Bartlesville |
| Top of Core | 2350.0 |
| Bottom of Core | 2382.0 |
| Top of Sand | 2351.0 |
| Bottom of ^{good} Sand | 2366.5 |
| Total Feet of Permeable Sand | 16.0 |
| Total Feet of Floodable Sand | 14.0 |

| Distribution of Permeable Sand: Permeability Range Millidarcys | Feet | Cum. Ft. |
|--|------|----------|
| 0 - 5 | 2.5 | 2.5 |
| 5 - 10 | 4.9 | 7.4 |
| 10 - 25 | 1.6 | 9.0 |
| 25 - 50 | 5.0 | 14.0 |
| 50 & above | 2.0 | 16.0 |

| | |
|---|--------|
| Average Permeability Millidarcys | 24.4 |
| Average Percent Porosity | 15.9 |
| Average Percent Oil Saturation | 28.7 |
| Average Percent Water Saturation | 41.9 |
| Average Oil Content, Bbls./A. Ft. | 353. |
| Total Oil Content, Bbls./Acre | 5,822. |
| Average Percent Oil Recovery by Laboratory Flooding Tests | 3.6 |
| Average Oil Recovery by Laboratory Flooding Tests, Bbls./A. Ft. | 47. |
| Total Oil Recovery by Laboratory Flooding Tests, Bbls./Acre | 575. |
| Total Calculated Oil Recovery, Bbls./Acre (Primary & Secondary) | 3,739. |
| Packer Setting, Feet | |
| Viscosity, Centipoises @ | |
| A. P. I. Gravity, degrees @ 60 °F | |
| Elevation, Feet | |

A fresh water mud was used as a circulating fluid in the coring of the sand in this well. The well was drilled in a virgin area. The core was sampled and sealed in tin cans by an employee of Oilfield Research Laboratories.

FORMATION CORED

The detailed log of the formation cored is as follows:

| <u>Depth Interval,</u> <u>Feet</u> | <u>Description</u> |
|---------------------------------------|---|
| 2350.0 - 2351.0 | - Shale, containing a vertical fracture. |
| 2351.0 - 2366.5 | - Light brown, slightly shaly sandstone. |
| 2366.5 - 2367.5 | - Brownish gray, shaly, carbonaceous sandstone. |
| 2367.5 - 2382.0 | - Sandy shale. |

Coring was started at a depth of 2350.0 feet in shale and completed at 2382.0 feet in sandy shale. This core shows a total of 16.5 feet of sandstone. The pay is made up of light brown, slightly shaly sandstone.

PERMEABILITY

For the sake of distribution, the core was divided into two sections. The weighted average permeability of the upper and lower sections is 35.2 and 5.8 millidarcys respectively; the overall average being 24.4 (See Table III). By observing the data given on the coregraph, it is noticeable that the sand has a very irregular permeability profile. The permeability of the sand varies from 0.97 to a maximum of 71. millidarcys.

PERCENT SATURATION & OIL CONTENT

The sand in this core shows a fairly low weighted average percent oil saturation, namely, 28.7. The weighted average percent oil saturation of the upper and lower sections is 29.0 and 28.3 respectively.

The weighted average percent water saturation of the upper and lower sections is 39.6 and 45.8 respectively; the overall average being 41.9 (See Table III). This gives an overall weighted average total fluid saturation of 85.4 percent.

In an effort to determine whether or not any flushing of the sand occurred during coring, all of the saturation samples were analyzed for chloride content. The results of these tests are given in Tables VI and VII. From the data given in these tables and on the coregraph, it is evident that considerable flushing of the sand did occur during coring as the zone of higher permeability had a much lower average chloride content.

The weighted average oil content of the upper and lower sections is 370 and 321 barrels per acre foot respectively; the overall average being 353. The total oil content, as shown by this core, is 5,822 barrels per acre (See Table III).

LABORATORY FLOODING TESTS

When taking into consideration that the sand in the core had a fairly low oil saturation, the samples responded rather well to laboratory flooding tests, as a total recovery of 575 barrels of oil per acre was obtained from 12.1 feet of sand. The weighted average percent oil saturation was reduced from 30.0 to 26.4, or represents an average recovery of 3.6 percent. The weighted average effective permeability of the samples is 1.15 millidarcys, while the average initial fluid production pressure is 33.8 pounds per square inch (See Table V).

By observing the data given in Table IV, you will note that of the 17 samples tested, 16 produced water and 13 oil. This indicates that approximately 76 percent of the sand represented by these samples is floodable pay sand.

CONCLUSION

From a study of the above data, we estimate that approximately 3,739 barrels of oil per acre or an average of 267 barrels per acre foot can be recovered from the area, represented by this core, by efficient primary and waterflood operations. Of this amount, 2,017 barrels can be expected from primary production and 1,722 from waterfloodings. The following data was used in calculating the above oil recovery values:

| | |
|--|------|
| Original formation volume factor | 1.22 |
| Irreducible water saturation, percent | 29.0 |
| Primary recovery, estimated, percent | None |
| Present oil saturation, percent | 58.2 |
| Average porosity, percent | 16.2 |
| Oil saturation after flooding, percent | 26.4 |
| Performance factor | 0.55 |
| Net floodable pay sand, feet | 14.0 |

This core shows a rather clean sand section having a fairly low oil saturation, a moderate water saturation and a good permeability for its depth.

The chloride tests indicate that considerable flushing of the sand occurred during coring. This would cause the sand in the core to show a lower oil and a higher water saturation.

Oilfield Research Laboratories

RESULTS OF SATURATION & PERMEABILITY TESTS

TABLE 1-B

Company Jackson Bros.

Lease Perrier

Well No. 6

| Sample No. | Depth, Feet | Effective Porosity Percent | Percent Saturation | | Oil Content Bbls. / A Ft. | Perm., Mill. | Feet of Sand | | Total Oil Content | Perm. Capacity Ft. X md. |
|------------|-------------|----------------------------|--------------------|-------|---------------------------|--------------|--------------|----------|-------------------|--------------------------|
| | | | Oil | Water | | | Ft. | Cum. Ft. | | |
| 1 | 2351.1 | 18.7 | 32 | 34 | 464 | 18. | 0.6 | 0.6 | 278 | 10.80 |
| 2 | 2352.0 | 14.6 | 26 | 49 | 294 | 3.1 | 0.5 | 1.1 | 147 | 1.55 |
| F-2 | 2352.2 | 16.9 | 28 | - | 367 | - | 0.5 | 1.6 | 183 | - |
| 3 | 2353.1 | 18.6 | 29 | 29 | 419 | 62. | 1.0 | 2.6 | 419 | 62.00 |
| 4 | 2354.1 | 13.4 | 31 | 44 | 322 | 6.6 | 1.0 | 3.6 | 322 | 6.60 |
| 5 | 2355.1 | 18.9 | 26 | 35 | 381 | 71. | 1.0 | 4.6 | 381 | 71.00 |
| 6 | 2356.1 | 16.4 | 27 | 40 | 343 | 48. | 1.0 | 5.6 | 343 | 48.00 |
| 7 | 2357.1 | 14.8 | 29 | 46 | 332 | 15. | 1.0 | 6.6 | 332 | 15.00 |
| 8 | 2358.1 | 16.9 | 27 | 40 | 354 | 36. | 1.0 | 7.6 | 354 | 36.00 |
| 9 | 2359.1 | 17.9 | 29 | 36 | 402 | 38. | 1.0 | 8.6 | 402 | 38.00 |
| 10 | 2360.1 | 16.4 | 29 | 45 | 368 | 40. | 1.0 | 9.6 | 368 | 40.00 |
| 11 | 2361.1 | 14.8 | 34 | 41 | 390 | 27. | 1.0 | 10.6 | 390 | 27.00 |
| 12 | 2362.1 | 14.4 | 27 | 42 | 302 | 4.3 | 1.0 | 11.6 | 302 | 4.30 |
| 13 | 2363.1 | 14.3 | 20 | 51 | 222 | 7.0 | 1.0 | 12.6 | 222 | 7.00 |
| 14 | 2364.1 | 13.4 | 32 | 53 | 332 | 7.3 | 1.0 | 13.6 | 332 | 7.30 |
| 15 | 2365.1 | 15.0 | 38 | 46 | 441 | 7.5 | 1.0 | 14.6 | 441 | 7.50 |
| 16 | 2366.1 | 16.6 | 21 | 39 | 270 | 8.0 | 0.9 | 15.5 | 243 | 7.20 |
| 17 | 2367.1 | 15.1 | 31 | 43 | 363 | 0.97 | 1.0 | 16.5 | 363 | 0.97 |
| Total | | | | | | | | | 5,822 | |

Oilfield Research Laboratories

SUMMARY OF PERMEABILITY & SATURATION TESTS

TABLE III

| Company | Lease | Well No. | | | | |
|-------------------------|--------------------------|---|---------------------------------------|--|---------------------------------------|------------------------------------|
| Jackson Bros. | Perrier | 6 | | | | |
| Depth Interval, Feet | Feet of Core Analyzed | Average Permeability, Millidarcys | Permeability Capacity Ft. x Md. | | | |
| 2351.0 - 2361.6 | 10.1 | 35.2 | 355.95 | | | |
| 2361.6 - 2367.5 | 5.9 | 5.8 | 34.27 | | | |
| 2351.0 - 2367.5 | 16.0 | 24.4 | 390.22 | | | |
| Depth Interval, Feet | Feet of Core Analyzed | Average Percent Porosity | Average Percent Oil Saturation | Average Percent Water Saturation | Average Oil Content Bbl./A. Ft. | Total Oil Content Bbls./Acre |
| 2351.0 - 2361.6 | 10.6 | 16.5 | 29.0 | 39.6 | 370. | 3,919 |
| 2361.6 - 2367.5 | 5.9 | 14.8 | 28.3 | 45.8 | 321 | 1,903 |
| 2351.0 - 2367.5 | 16.5 | 15.9 | 28.7 | 41.9 | 353 | 5,822 |

Oilfield Research Laboratories

RESULTS OF LABORATORY FLOODING TESTS

TABLE IV

| Sample No. | Depth, Feet | Effective Porosity Percent | Original Oil Saturation | | Oil Recovery | | Residual Saturation | | | Volumes of Water Recovered cc ^a | Effective Permeability Millidarcys ^{b,c} | Initial Fluid Production Pressure Lbs./Sq./In. |
|------------|-------------|----------------------------|-------------------------|--------------|--------------|--------------|---------------------|---------|--------------|--|---|--|
| | | | % | Bbls./A. Ft. | % | Bbls./A. Ft. | % Oil | % Water | Bbls./A. Ft. | | | |
| 1 | 2351.1 | 19.2 | 32 | 462 | 6 | 89 | 25 | 66 | 373 | 31 | 0.60 | 40 |
| 2 | 2352.2 | 16.9 | 28 | 367 | 2 | 26 | 26 | 71 | 341 | 60 | 1.20 | 30 |
| 3 | 2353.1 | 19.0 | 29 | 428 | 5 | 74 | 24 | 69 | 354 | 83 | 1.60 | 30 |
| 4 | 2354.1 | 13.7 | 31 | 330 | 1 | 11 | 30 | 53 | 319 | 9 | 0.10 | 50 |
| 5 | 2355.1 | 19.3 | 26 | 390 | 4 | 60 | 22 | 70 | 330 | 101 | 1.70 | 30 |
| 6 | 2356.1 | 16.8 | 27 | 352 | 3 | 39 | 24 | 70 | 313 | 59 | 1.90 | 30 |
| 7 | 2357.1 | 15.0 | 29 | 337 | 2 | 23 | 27 | 62 | 314 | 29 | 0.50 | 30 |
| 8 | 2358.1 | 16.9 | 27 | 354 | 2 | 26 | 25 | 69 | 328 | 31 | 0.50 | 40 |
| 9 | 2359.1 | 18.4 | 29 | 414 | 5 | 71 | 24 | 73 | 343 | 169 | 3.20 | 30 |
| 10 | 2360.1 | 16.9 | 29 | 381 | 5 | 66 | 24 | 68 | 315 | 119 | 2.30 | 30 |
| 11 | 2361.1 | 14.9 | 34 | 393 | 6 | 69 | 28 | 61 | 324 | 35 | 0.60 | 30 |
| 12 | 2362.1 | 14.6 | 28 | 318 | 0 | 0 | 28 | 59 | 318 | 15 | 0.20 | 40 |
| 13 | 2363.1 | 14.7 | 22 | 251 | 0 | 0 | 22 | 61 | 251 | 19 | 0.30 | 30 |
| 14 | 2364.1 | 13.9 | 32 | 345 | 1 | 11 | 31 | 60 | 334 | 24 | 0.30 | 30 |
| 15 | 2365.1 | 15.2 | 38 | 448 | 5 | 59 | 33 | 52 | 389 | 17 | 0.30 | 40 |
| 16 | 2366.1 | 16.5 | 22 | 282 | 0 | 0 | 22 | 68 | 282 | 15 | 0.20 | 40 |
| 17 | 2367.1 | 14.7 | 29 | 331 | 0 | 0 | 29 | 61 | 331 | 0 | Imp. | -- |

Company Jackson Bros. Lease Perrier Well No. 6

Notes: cc—cubic centimeter.

^a—Volume of water recovered at the time of maximum oil recovery.

^{b,c}—Determined by passing water through sample which still contains residual oil.

Oilfield Research Laboratories

SUMMARY OF LABORATORY FLOODING TESTS

TABLE V

| Company | Lease | Perrier | Well No. |
|---|-----------------|-----------------|-----------------|
| Jackson Bros. | 2351.0 - 2361.6 | 2361.6 - 2367.5 | 2351.0 - 2367.5 |
| Depth Interval, Feet | 10.1 | 2.0 | 12.1 |
| Average Percent Porosity | 16.9 | 14.5 | 16.5 |
| Average Percent Original Oil Saturation | 29.0 | 35.0 | 30.0 |
| Average Percent Oil Recovery | 3.7 | 3.0 | 3.6 |
| Average Percent Residual Oil Saturation | 25.3 | 32.0 | 26.4 |
| Average Percent Residual Water Saturation | 66.3 | 56.0 | 64.6 |
| Average Percent Total Residual Fluid Saturation | 91.6 | 88.0 | 91.1 |
| Average Original Oil Content, Bbls./A. Ft. | 380. | 396. | 382. |
| Average Oil Recovery, Bbls./A. Ft. | 50. | 35. | 47. |
| Average Residual Oil Content, Bbls./A. Ft. | 330. | 361. | 335. |
| Total Original Oil Content, Bbls./Acre | 3,839. | 793. | 4,632. |
| Total Oil Recovery, Bbls./Acre | 505. | 70. | 575. |
| Total Residual Oil Content, Bbls./Acre | 3,334. | 723. | 4,057. |
| Average Effective Permeability, Millidarcys | 1.32 | 0.30 | 1.15 |
| Average Initial Fluid Production Pressure, p.s.i. | 33.6 | 35.0 | 33.8 |

NOTE: Only those samples which recovered oil were used in calculating the above averages.

Oilfield Research Laboratories
RESULTS OF WATER DIFFERENTIATION TESTS
TABLE VI

Company Jackson Bros. Lease Perrier Well No. 6

| Sample No. | Depth, Feet | Chloride Content of Brine in Sand ppm | Percent Water Saturation | |
|------------|-------------|---------------------------------------|--------------------------|--------------------|
| | | | Connate | Drilling & Foreign |
| | | | Total | |
| 1 | 2351.1 | 60,400 | | |
| 2 | 2352.0 | 85,700 | | |
| 3 | 2353.1 | 21,800 | | |
| 4 | 2354.1 | 63,100 | | |
| 5 | 2355.1 | 11,725 | | |
| 6 | 2356.1 | 18,075 | | |
| 7 | 2357.1 | 89,300 | | |
| 8 | 2358.1 | 23,050 | | |
| 9 | 2359.1 | 17,025 | | |
| 10 | 2360.1 | 21,500 | | |
| 11 | 2361.1 | 54,175 | | |
| 12 | 2362.1 | 95,000 | | |
| 13 | 2363.1 | 89,750 | | |
| 14 | 2364.1 | 105,100 | | |
| 15 | 2365.1 | 98,500 | | |
| 16 | 2366.1 | 85,300 | | |
| 17 | 2367.1 | 87,600 | | |

Note: ppm — parts per million

Oilfield Research Laboratories

SUMMARY OF WATER DIFFERENTIATION TESTS

TABLE VII

Company Jackson Bros. Lease Perrier Well No. 6

| <u>Depth Interval, Feet</u> | <u>Chloride Content of Brine in Sand, ppm</u> | <u>Average Percent Connate Water</u> | <u>Average Percent Drilling & Foreign Water</u> |
|---------------------------------|---|--|---|
| 2351.0 - 2361.6 | 37,606 | | |
| 2361.6 - 2367.5 | 93,686 | | |
| 2351.0 - 2367.5 | 57,659 | | |

Note: ppm — parts per million.