

Farm McCall

No. 1

Total Depth 813+5

Comm. 6-25-54

Comp. 7-1-54

Shot or Treated Dry

Contractor Lacey & Johnson

Issued



	Casing	
20 in.	10 in	---7'
15 1/2	8 1/4	---reduced to 8 1/4, but not run.
12 1/2	6 5/8	---647'
13 3/8	5 3/16	

Elevation

Production Dry

Figures Indicate Bottom of Formation

7	soil and clay	7	18	shale light	597
8	sand rock	15	17	lime	614---20'
8	lime	23	6	slate	620--water
12	shale gray	35	4	lime	624--5'
7	shale sandy	42	16	shale sandy light	640
13	lime	55	7	shale dark	647
42	shale dark	97	17	shale dark	664
9	lime	106	3	shale sandy	667
15	shale dark	121	4	shale dark	671
59	lime	180	3	shale light	674
6	shale dark	186	6	shale dark	700
4	lime	190	5	shale sandy	705
3	shale dark	193--gas	16	shale dark	721
4	lime	197	10	shale sandy	731
2	shale dark	199--water	19	shale dark	750
25	lime	224	6	shale light	7 56
2	sand	226	3	shale dark	759
14	lime	240	5	shale sandy light	764
2	shale light	242	7	gas sand	771--no gas
13	lime	255	12	shale sandy dark	783
4	sand	259	16	shale dark	799
2	shale light	261	5	shale light	804--gas odor
2	lime	263	2.5	sand	806.5
50	shale light	313	2	sand gray oil	808.5
4	shale dark	317	4	shale light	812
8	lime shells	385	1.5	shale black	813.5
3	lime	388			
24	shale light	412			
8	shale dark	420			
6	shale light	426			
14	lime	440			
4	shale	444			
11	lime	455			
28	shale light	483			
2	lime	485			
8	shale light	493			
26	shale sandy	519			
31	lime	550			
3	shale dark	553			
6	lime	559			
20	shale dark	579			

Tested 2 gal. oil
 2 AM to 9 AM
 Abandoned.