

Dietrich Farm  
Well No. 17

State of Kansas  
Allen County  
Northwest Quarter of Northwest Quarter  
Section 22-26-18  
395 feet east of west line  
800 feet south of north line  
Commenced spudding February 28, 1957  
Finished drilling March 7, 1957

*Leckman 7*

Thickness of Strata	Formation	Total Depth	Remarks
17	Lime	17	8 1/4" Drive Pipe set at 10 ft.
25	Shale	42	
14	Lime	56	
38	Shale	94	
148	Lime	242	
3	Black Shale	245	
28	Lime	273	6 5/8" pipe set at 287 feet.
92	Shale	365	
15	Sand	380	
27	Shale	407	
33	Lime	440	30 ft.
5	Shale	445	
10	Sand	455	
60	Shale	515	
36	Lime	551	40 ft.
29	Shale	580	
20	Lime	600	
3	Black Slate	603	Little water
6	Lime	609	
26	Sandy Shale	635	
30	Shale	665	
3	Lime	668	
22	Shale	690	
2	Lime	692	
63	Shale	755	
5	Oil Sand	760	Light Showing.
5	Broken Sand	765	
35	Shale	800	SLM 805'. Hole 7' long. Started coring at 805'.
5	Oil Sand	805	
3 1/2	Broken Sand	808 1/2	
3	Oil Sand	811 1/2	Bleeding
5	Oil Sand	816 1/2	Bleeding.
4 1/2	Oil Sand	821	Bleeding.
4	Oil Sand	825	Bleeding.
1 1/2	Sandy Shale	826 1/2	
1	Oil Sand	827 1/2	
3	Black Sand	830 1/2	
Total Depth		830.5	

1 - 6 1/4" Rubber Packer set at 809'  
1 - 2" Seating Nipple set at 820'  
15 Sacks of Cement run on packer

-Material used in hole-

1 - 6 1/4" Rubber Packer ~~KM1 GCEXXXXXHWX~~  
8 1/4" Drive Pipe 10'  
2" Tubing 832'  
1" Tubing 827'  
1 - 2" Seating Nipple  
1 - 2" Cage  
1 - 2" Perforation  
1 - 2" Working Barrel