

DEEPWATER RECORD.

AYLWARD- SHELL PETRO.
 H. Erdwien No. 2

SEC. 11 T. 26 R. 2E
 NE SW SW
 945' WL. 973' SL

Total Depth. 3313
 Comm. 3-6-34 Comp. 4-19-34
 Shot or Treated. 1000 gal acid.
 Contractor. J. A. Aylward.
 Issued. 10-10-32

County. Sedgwick.



CASING.

133/8" 187' 7" 2857'
 10 3/4" 1402' 5 1/8" 3095'
 85/8" 2485'

Elevation.

Production. Potential

Figures Indicate Bottom of Formations. 323 bbls Oil. Est 850B.W.
 24 hours.

shale	HFV 50	70	shale	965	lime	1880
lime		90	lime	975	shale	1905
shale		100	shale	1005	shale	2005
gypsum		115	sand 5 BWPHR 1005-20	1020	lime	2025
shale		160	lime	1030	shale	2050
lime		170	shale	1060	lime	2070
shale		184	lime	1070	red rock	2080
lime		187	red rock	1075	shale	2085
shale		192	shale	1090	lime	2115
red rock		200	lime	1100	shale	2170
shale		215	shale	1110	lime	2175
lime		240	lime	1120	shale	2190
shale		255	shale	1150	lime	2230
red rock		270	lime	1175	lime	2290
lime		290	shale	1180	shale	2305
lime		310	lime	1190	lime	2330
lime and shale breaks		370	shale	1200	shale	2345
lime		420	lime	1220	shale and shells	2395
shale		425	shale	1230	show oil 2455 5 BW 2455-	
red rock		445	lime	1245	2460	
lime		455	shale	1250	shale and shells	2395
shale		485	lime	1260	lime	2485
sdv lime		495	shale	1350	lime	2565
lime		510	sand	1380	shale	2615
red rock		517	shale	1390	sdv shale	2625
lime		530	lime	1402	lime	2650
shale		540	lime	1410	shale	2660
lime		560	shale	1415	1/2 BWPHR 2615-2625	
shale		570	lime	1430	lime	2685
lime		580	shale	1445	shale	2700
shale		585	lime	1480	lime	2705
red rock		590	shale	1485	lime	2735
lime		640	lime	1535	shale	2740
shale		650	shale	1555	lime	2800
lime		660	lime	1580	shale	2810
shale		665	lime	1585	lime	2815
lime		700	shale	1595	shale	2825
shale		710	lime	1630	V.C. shale	2845
lime		725	shale	1640	V.C. shale	2852
shale		730	lime	1660	show oil 2855-2857	
lime		745	shale	1670	chat	2857
shale		750	lime	1690	335' water and 5 B.O.	
lime		780	shale	1700	in 30 min. HFV 2857-60	
shale		810	lime	1710	chat	2860
lime		820	shale	1715	lime	2975
shale		827	lime	1725	lime	3118
lime		835	shale	1730	shale	3170
shale		850	lime	1745	lime	3172
lime		865	shale	1750	show oil and water T.D.	
shale		875	lime	1775	3170-72. 350' oil and	
lime		885	shale	1780	350' water 3 hours.	
shale		895	lime	1800		
shale		915	shale	1805	4-13-34. Pump 45 bbls	
red rock		925	lime	1855	oil with no est water in	
lime		955	shale	1860	4 hours. OVER	

Deepening Record.

11-26-2E
NE SW SW
H. Erd. well No. 2

Sedgwick. County

117476

Aylward Production Co.

Comm. 5-5--42

Comp. 7-20-42

Prod. 23bbbls.

5 $\frac{1}{2}$ " 3284

Lime	3172-3225	HFV
sdv lime	3243	
lime	3253	
shale	3256	
lime	3272	
shale	3275	
sdv lime	3297	
lime	3310	
SLMC	3313	

Total Depth.