

15-26-2E

WELL LOG

State Geological Survey
WICHITA, BRANCH

SHELL, K. F. FISCHER NO. 10
SE NE SW SE SECTION 15-26S-2E
1080' fr WL 870' fr SL
GREENWICH FIELD, SEDGWICK CO., KANSAS

Total Depth 3204
Comm. 6-8-35 Comp. 7-9-35
shot or Treated. 1000 gal acid.
Contractor.
Issued. 7-27-35.

Casing: 13-3/8" 91'
7" 3181'

Production: 1016 B. 72 Hrs.
Pumping

Figures Indicate Bottom of Formations.

soil	75	3150 equals 3154 S.L.C.
lime shells	91	shale 3181
anhydrite	140	shell lime hard 3182
anhydrite & shale	197	standardizing.
shale & shells	375	shale blk 3202
shale & lime	461	chert 3202'2"
shale and shells	573	dolomite show of oil 3204 T.D.
lime and shale	745	hole filled up 860' of oil and
lime	843	260' of water in 6 hours at 3204.
shale and shells	1267	
shale and shells	1416	7-10-35. Swabbed 115 bbls. oil and
lime	1442	65 bbls. water in 18 hours.
shale and lime	1464	
lime	1478	7-13-35. Swabbed 445 bbls. oil and
broken lime and shale	1525	460 bbls. water in 10 1/2 hours.
shale	1540	
shale & lime shells	1638	339 B.O. and 1230 B.W. 3 day
lime and shale	1766	average (pumping).
shale and shells	1861	
lime and shale	1973	
shale & lime shells	2067	
lime	2136	
lime and shale	2264	
lime	2346	
lime	2394	
lime and shale	2431	
shale and shells	2497	
lime and shale	2607	
lime	2646	
broken lime	2750	
lime and shale	2841	
lime and shale	2882	
Var. ool shale	2899	
chat soft	2910	
chat hard	2913	
chat soft	2930	
chat soft	2934	
chat hard	2950	
chat	3002	
chat hard and sharp	3022	
lime	3031	
lime hard	3056	
lime	3089	
lime brown	3108	
shale	3150	