

GYPSY OIL COMPANY.  
 Urban No. 23

SEC. 11 T. 26 R. 4E.  
 SEC NE NW

Total Depth. 2020' P.B. 2011.  
 Comm. 6-14-34 Comp. 8-14-34  
 Shot or Treated. 1000 gal acid.  
 Contractor.  
 Issued. 12-15-34.

County. Butler.

C.SING.



12 1/2" 91' 65/8" 1657' rerun at 1950'  
 10" 615' UR 835'  
 8 1/2" 1285' UR 1520'

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

lime	65	lime	1110	lime	1991
shale	95	shale	1120	Acidized 1000 gal. @ 1991 8-5-34	
lime	105	lime	1135	Pump 58 B.O. & 22 BW 19H. 8-8-34	
sand	110	shale	1150	Pump 5 B.O. & 1 1/2 BW 8H. 8-9-34	
1 BW 105-108		lime	1167	lime	1996
red rock	118	shale	1175	no increase.	
lime	160	lime	1195	lime	2001
shale	175	HFW 1180-85		Pump 14 B.O. & 4 BW 31 hrs.	
lime	185	shale	1215	sdv lime	2020
shale	195	lime	1260	6 BWP.	
lime	210	shale	1266	Total Depth.	
shale	220	lime	1300	Plug back to 2011.	
lime	230	1 BW 1280-85		Bailed at intervals for several	
shale	240	shale	1320	days recovered mostly water	
lime	250	lime	1325	and a little oil.	
shale	290	shale	1340		
lime	305	lime	1390	Hole plugged and abd. 8-29-34.	
shale	310	small show gas	1350-55		
lime	330	broken lime	1410	Dry and Abd.	
2 BW 315-20		shale	1430		
shale	340	sdv lime	1460		
sdv lime	350	shale	1465		
shale	355	sdv lime	1520		
lime	370	2 BW 1465-95			
shale	375	shale	1565		
lime	385	<u>SAMPLE LOG</u>			
shale	395	lime	1572		
lime	415	shale	1578		
shale	420	sand	1585		
lime	425	sdv shale	1595		
shale	430	lime	1596		
lime	450	sand	1605		
shale	455	lime	1621		
lime	465	shale	1655		
shale	535	small show oil	1704-11		
red rock	545	lime	1736		
shale	550	show oil & water	1734-36.		
red rock	555	bailed 13 1/2 bailers oil and			
shale	605	2 1/2 Bailers Wtr. in 17 hours.			
lime	625	Acidized 1000 gal. 7-20-34.			
shale	745	Pump 20 B.O. & 135 B.W. 24 hrs. 7-24-34			
lime	770	Pump 20 B. O. & 187 B. W. 24 Hr. 7-25-34			
shale	775	Pump 10 B. O. & 166 B. W. 24 Hr. 7-26-34			
lime	800	Pump 2 1/2 B.O. 137 B.W. 24 Hrs. 7-27-34.			
HFW 790-800		lime	1747		
sand	805	No increase. Pulled 6" and			
lime	820	straight reamed hole to 1743			
shale	834	lime	1815		
lime	840	shale	1952		
shale	865	lime	1976		
broken lime	985	Trace of oil	1967-69		
shale	1000	Trace of oil	1976-85		
sand	1005	Free oil	1985-87		
7 BW 1000-1005		lime and chert	1987		
shale	1040	After standing 8 hours, bailed			
lime	1060	1 bailer oil and 1/2 B.W.			
shale	1081	lime	1989		
lime	1098	after standing 16 hours bailed			
shale	1100	2 Bailers oil and 24 feet of wtr.			