

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.  
412 Union National Bank Bldg, Wichita, Kansas.

SINCLAIR PRAIRIE OIL CO.  
Ora Graham No. 8

SEC. 4 T. 26 R. 5E.  
SW NE SE  
330'f SL 330' WL NE  $\frac{1}{4}$  SE  $\frac{1}{4}$

Total Depth. 2619  
Comm. 4-15-40 Comp. 5-16-40  
Shot or Treated. 2000 gal.  
Contractor.  
Issued. 2-22-41

County Butler.

CASING.

16" 82'  
13" 632'  
10 3/4" 1612'  
7" 2603' cemented.

Elevation.

Production. 77 bbls.

Figures Indicate Bottom of Formations.



soil	3	lime	992	shale	2601
lime	75	shale	1000	lime Viola	2619
shale	88	lime	1010		
lime	120	shale	1020	Total Depth.	
red rock	125	lime	1055		
lime	160	shale	1120	Some wtr 75'	
lime sdy	165	lime	1155	1 BWP 345-350	
red rock	175	shale	1165	1 BWP 525	
shale	205	lime	1195	3 BWP 975-985	
lime	225	shale	1205	2 BWP 1810-1815	
slate shells	245	lime	1225	1 1/2 BWP 2310	
red rock	250	shale	1230	hole caving 2525-2550	
lime	255	lime	1240		
shale	260	shale	1245		
shale&shells	300	lime	1250	Top sand 2601	
lime	310	shale	1265	Bottom sand 2619.	
redrock	315	lime	1380		
lime	350	shale	1430	Well Not shot.	
shale	355	lime	1475		
lime	365	shale	1485		
shale	370	lime	1510		
lime	460	shale	1525		
shale	465	lime	1540		
lime	495	shale	1660		
shale	515	lime	1680		
lime	525	shale	1685		
shale	545	lime	1695		
lime	550	shale	1755		
shale	575	lime	1900		
lime	600	shale	1925		
shale	605	lime	1970		
lime	615	shale	2045		
shale	620	lime	2150		
lime	625	shale	2155		
shale	635	lime	2190		
lime	645	shale	2195		
shale	720	lime	2215		
lime broken	740	Note - SLM at this point			
shale	755	making correction from			
lime	775	cable line Measurement <del>2215</del> to 2193			
shale	790	lime	2198		
lime	825	shale	2264		
shale	830	lime	2279		
lime	885	shale	2310		
shale	895	lime	2340		
lime	900	shale	2355		
shale	925	lime	2385		
lime	928	shale	2390		
shale	960	lime	2420		
lime	965	shale	2475		
shale	975	lime	2485		
sand water	985	shale	2520		
shale	990	lime	2525		