

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.  
 Union National Bank Bldg, Wichita, Kansas

*J. E. Jamison*  
 plotted  
 19-26-8E

THE MOHAWK OIL CO. ET AL.  
 Overstreet No. 1.

SEC. 19 T. 26 R. 8E.  
 NW corner Lot 21.

DEEPENING RECORD


Total Depth. 3140' P.B. 2068'  
 Comm. 8-12-35 Comp. 10-1-35.  
 Shot or Treated. 1000 gal acid.  
 Contractor. The Mohawk Oil Co.  
 Issued. 8-8-36

AUG 8 1936

County. Butler.

CASING.

12 1/2" 555  
 10" 709'  
 stright reamed to 985  
 8 1/2" 1900'  
 6 5/8" 2053'  
 6" 2725'



Elevation.

Production. Pot. 100 bbls.

Figures Indicate Bottom of Formations.

clay yellow	35	lime hard	770	lime	1470
shale blue	55	shale	777	shale	1485
shale light	70	lime	793	lime	1490
lime grey	95	shale light	798	shale	1555
shale blue	105	lime	808	sand 1 1/2 BW 1555	1565
red rock	118	shale light	810	shale sand	1615
lime	145	lime hard	820	shale	1653
shale grey	150	shale soft	825	lime	1660
lime	155	lime hard	835	shale	1745
shale blue	160	shale soft	870	cave 1650-1670	
lime	170	lime soft	885	lime	1750
shale light	175	shale soft	915	shale	1752
lime grey	180	lime	922	lime	1765
shale	195	shale blue	945	lime light grey	1850
red rock	200	lime hard	950	lime hard	1895
shale blue	215	shale soft	970	shale	1897
lime grey	225	sand soft	985	lime	1907
2 BW 215-225		HFW 970-85		shale light	2052
shale	240			K.C. lime hard	2068
lime	253	lime	1000	Oil 2058-2067	
shale light	265	shale light	1055	Total Depth.	
lime	290	shale lime	1070		
shale grey	315	lime hard	1095	Initial production	
lime	320	shale light	1105	30 bbls nat before	
shale grey	345	lime	1115	treating with acid.	
lime grey	350	shale light	1125		
shale white	370	lime hard	1130		
shale blue	375	shale soft	1155		
lime wh hard	380	lime hard	1165		
shale blue	395	shale soft	1180		
lime	400	lime	1190		
shale blue	405	shale light	1200		
lime	418	lime	1205		
shale blue	475	shale cave 1212-15	1216		
shale light	505	lime	1225		
red rock	510	shale	1238		
shale	525	lime	1270		
red rock	535	shale soft	1280		
shale	555	little water 1265			
lime ha rd	558	shale and shells	1290		
shale	600	lime	1315		
shale sdy	625	shale light	1327		
little water 615		lime	1340		
shale light	645	1 BW 4 hrs 1290			
lime hard	650	shale	1395		
shale light	678	lime	1400		
sand	693	shale	1403		
HFW 678-93		lime	1415		
shale blue	708	shale	1420		
lime hard	712	lime	1427		
shale soft	735	shale	1430		
lime hard	737	lime hard	1435		
shale light	750	shale	1450		

(OVER) →

38 36-0

DEEPENING RECORD

The Mohawk Oil Co. et al  
 Overstreet No. 1. Prod. 10 B.F.D. after plugging back to 2068'  
 NW Cor Lot 21 19-26-8E Butler County.  
 Drlg. Cont. The Mohawk Oil Co.  
 Comm. 4-27-36 Comp. 5-19-36  
 Old Total Depth 2068' 6" Casing 2725'

lime	2075
lime hard	2158
shale	2160
lime hard	2175
lime soft	2185
lime med	2225
shale soft	2245
lime hard	2260
shale soft	2270
lime hard	2275
shale soft	2302
lime shell	2306
shale soft	2320
lime hard	2330
shale soft	2335
shale soft	2350
lime hard	2365
shale soft	2405
lime hard	2425
shale soft	2445
lime hard	2455
shale soft	2457
shale soft	2460
lime hard	2465
shale soft	2470
lime hard	2485
shale soft	2500
sdv shale	2520
shale soft	2610
sdv shale sft cave	2640
shale soft	2680
shale soft sandy	2705
shale	2725
lime hard	3075
5 BW 2750-2765	
4 BW 2962-2965	
broken lime soft	3040
break 3035-40	
lime	3070
shale soft	3075
shale	3130
sand	3134
sand hard HFW	3140
Total Depth	

Plugged back to 2068'.