

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY

19-27-2E
42266

UNION NATIONAL BANK BLDG WICHITA KANSAS.

Location NE NW NE Sec.19 T. 27 R. 2E

348' of NL & 1378' of EL NE/4 DRL

Casing Record 10" 1923'3" Farm- Eastborough Estates 1-10-08 County- Sedgwick. No. 4


20" 30 8 1/4" 2768 Company- Derby Oil Co.

15" 65 65/8" liner 200 Contr.- Greenwich Drilling Co.

12" 1195' 5 3/16" Comm.- 9/27/1930. Comp.- 10/27/1930

Total Depth 2975' Shot Quarts Between

Correspondence Regarding This Well Should Be Referred to



Figures Indicate Bottom of Formations.
Date Issued. 12/6/1930'.

Initial Production
80 bbls per hr.

Elevation

Formation	Depth	Formation	Depth	Formation	Depth
mud yellow sft	30	shale blue sft	1410	chat	2965
shale blue sft	65	lime hrd	1435	chat	2967
shale shells	225	lime shells	1450	chat sft	2972 1/2
shale blue sft	230	shale blue sft	1485	chat	2975
lime gray hrd	245	slate black sft	1495		
shale blue sft	255	lime gray hrd	1500	Total Depth	2975'
lime gray hrd	260	shale black sft	1540		
shale blue sft	270	2 BW 1560-1565'			
lime gray hrd	285	lime shells hrd	1560		
shale lgt blue sft	290	sdv lime hrd	1595		
shale gray sft	305	shale sft	1620		
shale brown sft	350	lime gray hrd	1625		
lime lgt hrd	365	shale blue sft	1635		
shale blue sft	370	lime gray hrd	1660		
lime gray hrd	385	shale black sft	1665		
shale blue sft	390	lime brown hrd	1690		
lime gray hrd	450	shale black sft	1765		
shale blue sft	460	lime gray hrd	1775		
lime gray hrd	475	shale blue sft	1780		
shale blue sft	480	lime gray hrd	1790		
lime gray hrd	495	shale blue sft	1800		
1/2 BW at 485'		lime gray hrd	1912		
shale shells, shale		sdv shale brown sft	1970		
blue sft	520	lime gray	1980		
brkn lime drk hrd	580	sdv shale blue sft	1990		
lime gray hrd	595	lime gray	1995		
red rock sft	607	shale blue sft	2170		
lime gray hrd	610	lime gray hrd	2180		
lime blue hrd	620	lime gray hrd	2225		
shale black sft	630	shale blue sft	2335		
brkn lime	665	lime gray hrd	2340		
shale brown sft	675	shale black sft	2435		
brkn lime lgt hrd	750	lime gray hrd	2440		
shale shells brown	825	shale drk sft	2450		
lime gray hrd	840	brkn lime gray sft	2500		
shale shells	1000	lime gray hrd	2565		
shale	1015	4 BW 2565 to 2575'			
lime	1025	sdv lime white sft	2575		
shale	1045	lime gray hrd	2680		
lime	1050	shale blue sft	2685		
shale	1085	lime gray hrd	2690		
lime gray hrd	1090	shale drk sft	2725		
shale	1095	lime brown hrd	2740		
lime	1100	shale black sft	2765		
shale blue sft	1140	lime white hrd	2785		
lime	1150	Bailed hole dry			
3 BW per hr 1140-1150'		shale black sft	2805		
shale drk sft	1165	lime gray hrd	2820		
HW 1165 to 1175'		shale shells	2840		
wet sand lgt sft	1175	lime lgt hrd	2850		
lime gray hrd	1185	shale black sft	2855		
shale brown sft	1225	lime lgt hrd	2865		
lime gray hrd	1230	shale brown sft	2880		
shale blue sft	1250	shale shells	2895		
Bailed hole dry		shale brown sft	2905		
lime gray hrd	1260	lime white hrd	2910		
shale blue sft	1285	shale blue sft	2945		
lime lgt hrd	1295	various col. shale	2950		
shale brown sft	1310	shale & lime	2960		
lime lgt hrd	1330	chat very sft	2963		
		Oil from 2960-2963'			