

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY  
 Union National Bank Bldg, Wichita, Kansas

THE DICKEY OIL COMPANY,  
 Brown No. 2

SEC. 20 T. 28 R. 1E.  
 NW SW NE

CORRECTED LCG

Total Depth, 3163  
 Comm. 1-7-35 Comp. 1-30-35  
 Shot or Treated,  
 Contractor,  
 Issued, 6-15-35

County, Sedgwick.



CASING.

65/8" 3096'

Elevation.

Production. Pot. 831 B.

Figures Indicate Bottom of Formations.

sand	45	broken lime	2745
shale	80	lime	2755
lime	82	lime and shale	2775
lime shells and sand	157	lime hard	2790
broken lime	340	shale and lime	2795
lime	370	lime	2827
broken lime	420	shale and shells	2942
shale and shells	470	broken lime	2974
lime	510	shale and shells	3056
shale and lime shells	585	lime	3059
red bed	595	shale	3070
lime shells	630	lime	3076
lime	655	red bed	3086
red bed	665	lime shells	3087
broken lime	765	shale	3095
shale and shells	845	red rock	3097
lime	890	shale	3100
shale and shells	970	lime white	3102
shale	1050	shale yellow	3112
lime	1060	shale grey	3120
shale	1220	lime yellow	3124
shale and shells	1270	red rock	3128
broken lime	1310	lime chatty	3129
shale and shells	1360	chat	3136
lime	1380	chat and lime	3155
shale and lime shells	1440	chat brown lime	3163
shale	1460	Total Depth.	
shells	1500		
shale	1540	Increase oil	3134.
shale shells	1670	Used Rotary tools.	
lime	1680		
shale and shells	1737		
broken lime	1775		
shale	1793		
broken lime	1875		
lime	1915		
broken lime	1990		
shale and shells	2275		
lime	2280		
lime shells	2300		
shale	2360		
lime	2370		
shale	2400		
lime	2415		
shale	2480		
broken lime	2500		
shale	2540		
shale shells	2585		