

J. H. WAGNER DRILLING COMPANY

COMPANY. **Doyle & Leslie**

FARM. **Stryker**

WELL NO. **2**

TOTAL DEPTH **1295**

COMM. **2/11/54**

COMP. **2/25/54**

CONTRACTOR:

**J. H. WAGNER Box 751
El Dorado, Ks.**

ISSUED:

3/3/54

SEC. **2** TWP. **23** R. **13**

DESC. **SW 34**

COUNTY **Wilson** KANSAS

CASING RECORD:

8"	660'	Pulled
7"	913'	Pulled
5 1/2"	1291'	Cemented w/15 ex
7"	94.70'	Surface Casing

ELEVATION. **---** PRODUCTION. **---**

(FIGURES INDICATE BOTTOM OF FORMATION)

Soil	1	Shale, dark	905
Sand rock	20	Lime	907
Sand	48	Shale, black	934
Shale, light	60	Shale, light	957
3 SW 60-72		Lime, gray	972
Shale, sandy	72	Shale, light	986
Shale, blue	80	Lime, gray	997
Sand, gray	92	Lime, white	1003
Reduced hole at 95'		Sandy Shale	1045
Shale, light	132	1 SW 1060-1070	
Lime, gray	137	Sand, gray	1077
Shale, light	141	Shale, black	1080
Lime, gray	146	Shale, light	1088
Shale, light	300	Lime, brown	1117
Shale, gray	330	Shale, black	1139
Lime, gray	365	Lime, gray	1145
1 SW 365-375		Lime, brown	1154
Lime, brown	390	Shale, black	1160
Shale, gray	395	Lime, white	1166
Shale & Shells	405	Sandy Shale	1200
Shale, blue	460	Shale, dark	1225
Lime, gray	485	Shale, light	1235
Shale, light	564	Lime, gray	1237
Lime, gray	570	Shale, light	1245
3 SW 590-610		Sandy Shale	1263
Lime, white	610	Shale, dark	1270
Lime, gray	618	Shale & Shells	1290
Shale, sandy	628	1 SW 1290-1295	
Sand, gray	645	2 OOPH 1290-1295	
Sandy Shale	654	Sand	1298
Shale & Lime	660	Cored 1295-1320.4	
Lime, gray	666	Shale, black	1306
Shale, gray	690	Sand, gray	1318
Lime, brown	700	Shale, black	1320
6 SW 725-747		PH 1320 to 1295 w/sand rock & cement	
Lime	745		
Lime, gray	794	Sand-free PDP	
Shale, black	796		
Lime	805		
Lime, sandy, gray	823		
HPH			
Lime, gray	855		
Shale, black	859		
Lime, gray	864		
Shale, black	865		
Lime, gray	880		
Lime, white	890		
Lime	902		