

Schermerhorn oil corp.

L-36 Hultine

comp. in 1959

107	Shale	76
64	Sandy Shale	67
2	Shale	25
13	Limey Shale	96
A	Black Shale	74
	Shale	98
	Limey Shale	1001 T.D.
21	Core	

6' - Hole to 980'

4' - Hole from 980 to 1001'

Plugged with 60 sacks of cement in bottom and spotted a plug from 380' to 230'

Set 15 foot of 7 3/4 surface and saved well for water well

Schermerhorn Oil Corporation

Hultine L-36

Section 8-28-17 Wilson County, Kansas

Rotary Commenced: 8-4-59

Ended: 8-7-59

Contractor: Eas Drilling Company, Inc.

Thickness Strata	FORMATION	Total Depth
2	Soil	2
4	Clay	6
10	Lime Shells	16
9	Lime	25
219	Shale	244
74	Lime	318
5	Shale	323
6	Lime	329
31	Shale	360
10	Lime	370
5	Shale	375
10	Lime	385
6	Shale	391
10	Lime	401
15	Shale	416
11	Lime	427
120	Shale	547
6	Lime	553
87	Shale	640
38	Lime	678
32	Shale	710
20	Lime	730
5	Shale	735
6	Lime	741
197	Shale	928
47	Sandy Shale	975
42	CORE	1017 T.D.

10' - Surface Pipe

2" N-40 pipe cemented at 1015.5' and perforated into the Lawrence sand