

Company V.R. WYATT

Farm HOBBS

#1


Sec. 25 T. 28 R. 23  
Location 4 1/2 Mi N of W edge of Girard  
County Crawford Kansas

Total Depth 556 feet

Comm. 20 August 1954 Comp. 22 August 1954

Contractor Walters Drilling Co. Inc.

(Pressure sand fractured)



Elevation. 1013 feet

0 to 420 ft. Old well

420	"	431	"	Shale, gray
431	"	433	"	Shale, black
433	"	473	"	Shale, gray, dark to light
473	"	476 1/2	"	Sandy shale
476 1/2	"	487	"	Coal (4")
477	"	480	"	Lime, broken
480	"	484	"	Sandy shale
484	"	490 1/4	"	Shale, gray
490 1/4	"	491	"	Coal
491	"	492	"	Shale, light gray
492	"	500	"	Lime, shale
500	"	509	"	Lime shale and sand streaks
509	"	529	"	Shale, with streaks of lime, broken
529	"	530	"	Lime, hard shale
530	"	531	"	Shale
531	"	532 3/4	"	Shale, dark
532 3/4	"	534 1/2	"	Coal (pyritic)
534 1/2	"	538	"	Shale, dark
538	"	541	"	Lime and chert (Mississippi)
541	"	542	"	Chert
542	"	556	"	Lime, Chert (alternating and irregular)

Total Depth (E.D.) 556 feet

Drilled during this operation only 136 feet.

Cored from 531 to 556 feet.