

REX & MORRIS ET AL
De Moss No, 3-B.

SEC. 5 T. 28 R. 7E
SW NW SE

Total Depth. 2742 $\frac{1}{2}$ '
Comm. 12-3-39 Comp. 1-30-40
Shot or Treated. 100 Qts. Nitro
Contractor. Rex & Morris Drlg. Co.
Issued. 3-23-40

County. Butler



CASING:

12 $\frac{1}{2}$ " 905' P
10" 1605' P
8 $\frac{1}{4}$ " 2190' P
7" 2706'

Elevation.

Production. 35 Bbls.

Figures Indicate Bottom of Formations.

cellar	8	lime & shale	1185
lime	16	lime	1200
shale	35	shale	1205
lime	45	lime	1225
shale	50	shale	1230
lime	60	lime	1260
shale	65	shale	1285
red rock	75	lime	1300
lime	85	hole caving	
shale	95	shale	1325
lime	100	hole caving	
reduced hole 108'		lime	1335
shale	120	shale	1385
red rock	130	lime $\frac{1}{2}$ BWPH 1405-10	1425
shale	160	shale	1440
shale & shells	210	lime sdy	1450
shale	225	lime 8BWPH 1440-50	1470
lime	235	shale	1500
shale	245	lime	1503
lime 1BWPH 255-65	270	shale	1515
red rock	275	shale sdy	1545
shale	285	more wtr	
lime	290	sand	1560
lime brkn	335	carrying 13 BWPH@	1560
shale	370	sand shale	1610
lime	380	shale sdy	1640
shale	390	shale	1665
lime	405	lime	1690
shale	430	shale	1750
slate & lime	500	lime 4BWPH 1810-25	1935
shale	560	6 $\frac{1}{2}$ BWPH 1910-20	
sand	575	shale sdy	2070
9 BWPH		lime 8BWPH 2115-25	2220
shale	655	shale lime HFW 2153	2225
lime	660	lime SSO 2250	2265
sand	675	shale	2340
shale	720	lime	2345
shale & shells	745	shale	2405
lime & shale brks	785	hole caving	
lime 2BW 810-15	830	lime	2415
shale	840	shale	2465
red rock	845	lime	2495
shale	855	shale lime	2500
shale sdy	880	lime brkn	2525
shale	890	shale	2672
lime	895	sand	2685
sand & shale	905	good smell oil	2672-85
shale	930	shale sdy	2706
lime	935	sand	2712
shale	940	sand	2712-2724
lime	955	smell oil	
shale	960	saturation	
lime	965	sand	2724-2735
shale	970	show free oil	
lime	995	8 hr-test @ 2735	
shale	1070	1 BW - 5 BO	
lime	1090	sand	2735-2739
shale	1098	showing oil	
lime	1103	sand grey	2739-2742 $\frac{1}{2}$
shale	1108	show wtr $\frac{1}{2}$ BWPH	
lime	1135	Total Depth.	