


ADAIR-MORTON  
 Brandt No. 15

SEC. 15 T. 28 R. 7E.  
 SW NW NE

Total Depth. 2738  
 Comm. 2-5-41 Comp. 3-5-41  
 Shot or Treated. acidized.  
 Contractor.  
 Issued. 3-29-41

County Butler.



CASING.

15 1/2" 39'  
 12 3/8" 823'  
 10" 1490'  
 8 1/4" 2160'  
 6 5/8" 2705'

Elevation.

Production. 161 B.

Figures Indicate Bottom of Formations.

cellar	10	lime	1200	HFW 40-50
lime	20	shale	1235	1 BW 185-200
shale	25	lime	1240	4 BW 700-10
red rock	40	shale	1290	HFW 1450-60
lime	60	lime	1325	1 BW 1670-80
shale	105	shale	1345	3 BW 2040-65
lime broken	125	red rock	1350	HFW 2065-75
shale	130	shale	1365	
lime	140	lime	1385	
shale	150	shale	1390	
lime	155	shale sdy	1450	
shale sdy	175	sand	1460	
shale	185	shale sdy	1480	
lime sdy	200	shale	1490	
shale	210	shale sdy	1520	
lime	240	shale	1575	
shale	245	lime	1580	
lime	255	shale	1585	
shale	260	lime	1600	
lime	270	shale	1655	
shale	280	lime	1820	
lime	290	shale	1965	
shale	300	lime	2110	
lime	320	shale	2125	
shale	330	lime	2135	
lime	335	2135 equals 2150 Corr.		
shale	380	shale	2250	
lime	385	lime	2255	
shale	415	shale	2270	
red rock	425	lime	2275	
shale	620	shale	2325	
lime	625	lime	2335	
shale	635	shale lime		
lime	655	shells	2355	
shale	675	shale	2395	
lime	720	lime	2400	
shale	775	shale	2410	
lime	780	lime	2440	
shale	820	shale	2450	
lime	825	lime	2455	
shale	830	shale	2510	
lime	850	shale shells	2530	
shale	855	lime shells and		
lime shells	890	shale	2550	
shale	960	shale	2580	
lime	970	shale sdy	2635	
shale	980	shale	2705	
lime	995	dolomite	2707	free oil
shale	1010	lime & dolomite	2712	light saturation
lime	1045	dolomite	2728	light saturation
shale	1060	lime	2738	
lime broken	1085	Total Depth.		
shale	1090			
lime	1125	Top Miss. 2705		
shale	1140			
lime	1150			
shale	1175			