

21-28-8E


WELL LOG BUREAU — KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company - TABLE MESA OIL CO.
Farm - Ferrell No. 19

SEC. 21 T. 28 R. 8E
CN/2 NE SW

Total Depth. 2768'
Comm. 7-29-49 Comp. 9-2-49
Shot or Treated. Acid w/3000 gals @ 2747', 3000 gals @ 2758'
Contractor. Rex and Morris Drlg.
Issued. 1-14-50

County. Butler
KANSAS



CASING:
13 3/8" 735' P 5 1/2" 2725' cem w/75 sx.
10" 1390' P 7" S.P. 76' filled w/mud
8" 1555' P

Elevation. _____

Production. Init. 35 bbls.

Figures Indicate Bottom of Formations.

collar	5	lime	1135	lime	2768
lime	20	shale	1165	Total Depth	
shale	25	lime	1185		
lime	30	shale	1190		
shale	35	lime	1195		
red rock	45	shale	1210		
shale, shells	105	shale, shells	1250		
red rock	110	shale	1280		
shale	125	lime	1310		
lime	135	shale S	1335		
shale	150	lime	1360		
lime	175	Cave 1340-55			
shale	180	shale	1390		
lime	190	shale S	1415		
red rock	195	shale sdy	1440		
lime	225	8BWP 1420-30			
shale	240	shale	1490		
red rock	245	shale sdy	1510		
lime	275	more water @ 1500'			
lime brkn	310	shale	1530		
lime	325	lime	1540		
shale	330	shale	1545		
lime	335	lime	1555		
shale	340	shale	1650		
lime	345	lime	1655		
shale	300	shale	1665		
shale, shells	435	lime brkn	1675		
shale	440	lime	1680?		
lime	445	1/2 BWP 1685-95			
shale	475	1 BWP 1700-10'			
shale, shells	490	shale	1975		
shale	590	lime brkn	1985		
lime	600	lime 1 BWP 2100-10'	2110		
shale	615	shale	2115		
shale, shells	640	lime	2175		
lime brkn	705	shale	2265		
lime 1 BWP 715-25'	725	lime brkn	2275		
shale	780	lime	2295		
shale, shells	790	shale	2315		
shale	820	shale, shells	2355		
lime	830	lime	2385		
shale	835	sand	2395		
lime	840	lime	2485		
shale	855	shale	2613		
lime	860	lime	2620		
lime shells	885	shale	2630		
shale	965	red rock	2640		
lime brkn	975	shale	2690		
lime	985	shells, shale	2715		
shale B	1000	shale	2717		
lime	1025	lime	2725		
shale	1040	some stains 2721-25			
lime	1055	chert, chat	2736		
shale	1070	2 gal free oil in 30 mins.			
lime	1080	dol. lime	2747		
shale	1085	10 gal oil in 1 hr	2736-38'		
lime 1/2 BWP 1090-95'	1095	inc in oil	2742'		
Caving 1090-95'		12 gal oil in 30 min @ 2747'			
shale S	1110				