



T28S R09E, Sec. 36  
Fuqua 10-36 28-9  
15-049-22397

# **CMS-300 CONVENTIONAL PLUG ANALYSIS**

**Layne Energy**  
Various Wells

15-049-22397 Fuqua 10-36 28-9  
T28S R09E, Sec. 36

**CL File Number: DEN-120035**

**Date: 5.9.2012**

This report is based entirely upon the core samples, soils, solids, liquids, or gases, together with related observational data, provided solely by the client. The conclusions, inferences, deductions and opinions rendered herein reflect the examination, study, and testing of these items, and represent the best judgement of Core Laboratories. Any reliance on the information contained herein concerning the profitability or productivity of any well, sand, or drilling activity is at the sole risk of the client, and Core Laboratories, neither extends nor makes any warranty or representation whatsoever with respect to same. This report has been prepared for the exclusive and confidential use of the client and no other party.



**CMS-300 CONVENTIONAL PLUG ANALYSIS**

| Sample Number |              | Well Name                                 | Depth (ft) | Net Confining Stress (psig) | Porosity (%) | Permeability     |           | b(air) psi | Beta ft(-1) | Alpha (microns) | Grain Density (g/cm3) | Footnote |
|---------------|--------------|---|------------|-----------------------------|--------------|------------------|-----------|------------|-------------|-----------------|-----------------------|----------|
|               |              |   |            |                             |              | Klinkenberg (md) | Kair (md) |            |             |                 |                       |          |
| 1             | 15-049-22397 | Fuqua 10-36 28-9<br>T28S R09E, Sec. 36    | 2234.60    | 800                         | 6.25         | 0.007            | 0.0147    | 30.65      | 8.90E+13    | 2.05E+03        | 2.589                 |          |
| 2             | 15-125-30117 | E. McCabe 2-16<br>T31S R14E, Sec. 16      | 1411.50    | Ambient                     | 15.70        | ***              | ***       | ***        | ***         | ***             | 2.672                 | (5)      |
| 3             | 15-125-30124 | R. Copenhagen 15-10<br>T32S R14E, Sec. 10 | 1416.70    | 800                         | 8.40         | 6.73             | 7.68      | 6.79       | 9.58E+09    | 2.08E+02        | 2.584                 | (1)      |

**Footnotes :**

- (1) : Denotes fractured or chipped sample. Permeability and/or porosity may be optimistic.
- (2) : Sample permeability below the measurement range of CMS-300 equipment at indicated net confining stress (NCS). Data unavailable.
- (3) : Denotes very short sample, porosity may be optimistic due to lack of conformation of boot material to plug surface.
- (4) : Sample contains bitumen or other solid hydrocarbon residue.
- (5) : Denotes sample unsuitable for measurement at stress. Porosity determined using Archimedes bulk volume at ambient conditions.  
Permeability greater than 0.1 mD measured using helium gas. Permeability less than 0.1 mD measured using nitrogen gas. All b values converted to b (air)



## APPENDIX A: EXPLANATION OF CMS-300 TERMS "b", "Beta, and "Alpha"

|                  |   |   |
|------------------|---|---|
| $K_{\infty}$     | = | Equivalent non-reactive liquid permeability, corrected for gas slippage, mD   |
| $K_{\text{air}}$ | = | Permeability to Air, calculated using $K_{\infty}$ and b, mD  |
| b                | = | Klinkenberg slip factor, psi  |
| $\beta$ (Beta)   | = | Forcheimer inertial resistance factor, $\text{ft}^{-1}$   |
| $\alpha$ (Alpha) | = | A factor equal to the product of Beta and $K_{\infty}$ . This factor is employed in determining the pore level heterogeneity index, $H_i$ . |
| $H_i$            | = | $\log_{10}(\alpha\phi/RQI)$ $\alpha$ , microns = $3.238E^{-9} \beta K_{\infty}$   |
| $\phi$           | = | Porosity, fraction  |
| RQI              | = | Reservoir Quality Index, microns  |
| RQI              | = | $0.0314(K/\phi)^{0.5}$  |

### For further information please refer to:

Jones, S.C.: "Two-Point Determination of Permeability and PV vs. Net Confining Stress" SPE Formation Evaluation (March 1988) 235-241.

Jones S.C.: "A Rapid Accurate Unsteady-State Klinkenberg Permeameter," Soc. Pet. Eng. J. (Oct. 1972) 383-397.

Jones, S.C.: "Using the Inertial Coefficient,  $\beta$ , To Characterize Heterogeneity in Reservoir Rock: SPE 16949 (September 1987).

Amaefule, J.O.; Kersey, D.G.; Marschall, D.M.; Powell, J.D.; Valencia, L.E.; Keelan, D.K.: "Reservoir Description: A Practical Synergistic Engineering and Geological Approach Based on Analysis of Core Data,": SPE Technical Conference (Oct. 1988) SPE 18167.



## CMS-300 CONVENTIONAL PLUG ANALYSIS PROTOCOL

### Sample Preparation

1.0" diameter plugs were drilled with liquid nitrogen and trimmed into right cylinders with a diamond-blade trim saw.

### Core Extraction

Plugs were cleaned in a Soxhlet extraction unit, cycling in a chloroform/methanol (87:13) azeotrope.

### Sample Drying

Samples were oven dried at 240° F to weight equilibrium (+/- 0.001 g).

### Porosity

Porosity was determined using Boyle's Law technique by measuring grain volume at ambient conditions & pore volume at indicated net confining stresses (NCS).

### Grain Density

Grain density values were calculated by direct measurement of grain volume and weight on dried plug samples.  
Grain volume was measured by Boyle's Law technique.

### Permeability

Permeability to air was measured on each sample using unsteady-state method at indicated NCS.

### Fluid Saturations

Fluid saturations were determined by the Dean Stark technique using the following fluid properties:

|       |                            |
|-------|----------------------------|
| Brine | 1.032 g/cc (50000 ppm TDS) |
| Oil   | 0.845 g/cc (36° API)       |