

Location: Near the Center of the NE 1/4 NW 1/4 of Section 34, Township 29 South, Range 10E

ELK DRILLING CO., INC.

HOWARD, KANSAS Drilled May, 1953.

3 Dunkleberger Lease , Drilled for Morrow & Co In- Put Well

Soil	4
Clay	I6
Shale	4I
Lime	55
Shale	68
Lime	75
Shale	85
Lime	I02
Shale	I07
Lime	II6
Shale	II8
Lime	I20
Shale	I27
Red Rock	I37
Lime	I45
Shale	I60
Sand	I75
Shale	I85
Lime	I92
Shale	202
Lime	2I2
Shale	2I6
Lime	220
Shale	226
Red Rock	252
Shale	275
Lime	272
Shale	327
Sand	340
Shale, I022-346 ft.	390
Lime	397
Shale	400
Lime	403
Shale	438
Red Rock	455
Shale	470
Lime	479
Shale	490
Red Rock	495
Shale	520
Red Rock	528
Lime	53I
Shale	544
Lime	550
Shale	573
Sand, 2 Bailers W.	592
Shale	676
Lime	684
Shale	7I4
Red Rock	724
Shale - set 8" 729	733
Lime	752
Shale	765

Lime	767
Shale	795
Lime	798
Shale	803
Lime	968
Shale	I092
Lime(Gas C)	III2
Shale	II28
Lime	II45
Shale	II49
Lime	II55
Shale	II60
Lime	II65
Shells	II75
Lime	I225
Lime	I28I
Shale	I283
Lime	I293
Lime Sandy	I300
Sand I300	I306

Big Lime, H.F. 830-45

Steel Line

RECEIVED
STATE CORPORATION COMMISSION
JUL 23 1973
CONSERVATION DIVISION
Wichita, Kansas

I306 good oil
I3II 17 Ft, Rich sand,
I3I7
I322
I323 1/2 T . D.

Filled up 200 ft. over Nite, before shot.
Shot from , I299 to I32I.
68 pts. S.N.G.

5 Casing set, I293-3"ft
Cemented with 35 Sks.

35 ft 12" pipe

8 and 10 in casing

Pulled

Oct-64 45 ft of 7" Cemented for
conductor