

Operator Name: Devon SFS Operating Inc. Lease Name: Velma John 20 Well #: 1
 Sec. 20 Twp. 29 S. R. 18 East West County: Neosho

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed. Attach copy of all Electric Wireline Logs surveyed. Attach final geological well site report.

Drill Stem Tests Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No <i>(Attach Additional Sheets)</i> Samples Sent to Geological Survey <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Cores Taken <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Electric Log Run <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <i>(Submit Copy)</i> List All E. Logs Run: GR, N, D, DIL, CBL	<input checked="" type="checkbox"/> Log Formation (Top), Depth and Datum <input checked="" type="checkbox"/> Sample Name Top Datum See Attachments
--	--

CASING RECORD <input checked="" type="checkbox"/> New <input type="checkbox"/> Used							
Report all strings set-conductor, surface, intermediate, production, etc.							
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
Surface	11"	8 5/8"	32 #/ft	23'	Portland	4	none
Production	7 7/8"	5 1/2"	14 #/ft	1,171'	Cl 'A'	170	ThickSet

ADDITIONAL CEMENTING / SQUEEZE RECORD				
Purpose:	Depth Top Bottom	Type of Cement	#Sacks Used	Type and Percent Additives
___ Perforate				
___ Protect Casing				
___ Plug Back TD				
___ Plug Off Zone				

Shots Per Foot	PERFORATION RECORD - Bridge Plugs Set/Type Specify Footage of Each Interval Perforated	Acid, Fracture, Shot, Cement Squeeze Record (Amount and Kind of Material Used)	Depth
4 spf	1,056'-1,068'-Riverton Coal		
4 spf	1,010'-1,012'- Rowe Coal	500 gl FeHCl, 35,826 gl, 12,500#20/40Sand	

TUBING RECORD		Size	Set At	Packer At	Liner Run	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
		2 3/8"	1,100'-EOT	N/A		
Date of First, Resumed Production, SWD or Enhr.			Producing Method			
5/23/02			<input checked="" type="checkbox"/> Flowing <input checked="" type="checkbox"/> Pumping <input type="checkbox"/> Gas Lift <input type="checkbox"/> Other (Explain)			
Estimated Production Per 24 Hours	Oil Bbls.	Gas Mcf	Water Bbls.	Gas-Oil Ratio	Gravity	
	N/A	1 Mcfd	110 bbls.	N/A	N/A	


Disposition of Gas METHOD OF COMPLETION Production Interval

Vented Sold Used on Lease Open Hole Perf. Dually Comp. Commingled _____
(If vented, Sumit ACO-18.) Other (Specify) _____



MOKAT DRILLING
Office Phone: (316) 879-5377

P.O. Box 590
Caney, KS 67333



Lease Velma John^{20c}

Well No. #1
County Neosho State KS
Type/Well
Depth 1176'
Hours
Date Started 2-4-02
Date Completed 2-6-02

Operator DEVON

Sec. 20

Twp. 29

Rge. 18

Job No.	Casing Used	23' 8 5/8"	Bit No.	Type	Size	From	To	Bit Record	Type/Well	Depth	Hours	Date Started	Date Completed
Driller	Waylon				7 7/8"					1176'		2-4-02	2-6-02
Driller													
Driller													

Formation Record

From	To	Formation	From	To	Formation	From	To	Formation	From	To	Formation	
0	2	overburden	485	544	sandy shale	768	789	sandy shale				
2	16	sand	544	549	lime	789	804	gas test 7# 1/4"				
18	77	sandy shale	549	550	coal	789	804	shale				
77	92	lime	550	581	lime	804	805	coal				
92	114	shale	581	596	shale	805	823	shale				
114	180	lime	596	622	gas test 1# 1/4"	823	824	coal				
180	181	coal	622	644	lime	824	843	shale				
181	194	shale	644	655	shale	843	844	coal				
194	229	sand	655	659	lime	844	906	sandy shale				
229	230	coal	659	661	shale	906	908	coal				
230	239	shale	661	662	coal	908	924	shale				
239	273	lime	662	664	sand	924	926	lime				
273	280	shale	664	664	gas test 6# 1/4"	926	927	coal				
280	342	lime	664	665	shale	927	1009	sandy shale				
342	362	shale	665	666	lime	966	1011	gas test 8# 1/4"				
362	363	coal	666	667	shale	1009	1011	coal				
363	364	lime	667	668	shale	1011	1064	shale				
364	398	sandy shale	668	669	sand	1041	1064	gas test 9# 1/4"				
398	402	lime	669	670	gas test 7# 1/4"	1064	1066	coal				
402	408	gray shale	670	740	sandy shale	1066	1067	coal				
408	420	lime	740	741	lime	1067	1076	shale				
420	434	shale	741	742	shale	1076	1108	gas test 10# 1/4"				
434	447	lime	742	743	coal	1076	1091	lime MISS				
447	451	blk shale	743	761	shale	1091	1106	gas test 6# 1/4"				
451	484	sandy shale'	761	762	lime	1106	1176	lime				
484	485	coal	762	766	shale							
			766	768	coal							

RECEIVED
KOC WICHITA

ORIGINAL