

R.L.HODGE ET AL.
Glaze No. 2.

SEC. 4 T. 29 R. 4E.
CEL NE SE

Total Depth. 2095
Comm. 5-9-35 Comp. 6-26-35.
Shot or Treated.
Contractor.
Issued. 8-24-35

County. Butler.



CASING.

10" 601'
8 1/4" 1378'
6 1/8" 1605'
5 3/16" 1767'

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

soil	30	lime	1285
gravel	35	shale	1300
HFW 35		lime	1310
formation reports lost from		shale	1320
35 to 260 ft.		lime	1325
lime	320	shale	1335
2 BW 310-320		lime	1355
shale	330	shale	1378
lime hard	365	lime	1382
shale	385	shale	1385
lime	405	lime	1415
shale	410	shale	1455
lime	430	lime	1515
shale and lime shell	470	6 BW 1455-60	
shale	555	shale	1585
shale soft	575	brown lime	1595
lime	580	HFW 1585-1596	
shale	600	shale	1660
9 BW 580-600		sdv shale white	1685
lime	602	HFW 1660-1665	
red rock	605	shale blk	1767
lime	610	lime	1802
shale	625	shale	1805
lime	630	lime	1806
shale	675	shale	1840
lime	680	lime	1895
shale	700	1 BW 1879-1891	
lime	710	shale	1910
shale	725	lime	1967
lime	730	shale	1973
shale	745	lime	2072
lime	755	shale	2082
shale	800	lime	2095
lime	825	HFW 2095	
shale	835	Total Depth.	
lime	865		
shale	875		
lime	885		
shale	890		
lime	895		
shale	915		
lime	920		
shale	935		
lime	945		
shale	975		
lime	1050		
2 BW 975-1000			
shale	1125		
lime	1155		
shale	1165		
lime	1180		
shale	1185		
lime	1210		
5 BW 1185-1195			
shale	1220		
lime	1250		
shale	1270		