

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY  
412 Union National Bk. Bldg., Wichita, Kansas


15-29-7E

Company - ADAIR-MORTON CO.  
Farm - Bennett No. 1.

SEC. 15 T. 29 R. 7 E  
S E NE SE

Total Depth. 3205'  
Comm. 8-22-44 Comp. 9-22-44  
Shot or Treated.  
Contractor.  
Issued. 10-7-44

County. Butler  
KANSAS



CASING:  
12" 915' 6" 2783'  
10" 1305'  
8" 1555' NR 1680'

Elevation. 1456

Production. Dry

Figures Indicate Bottom of Formations.

cellar	8	shale & shells	930	lime	1725	Trace of
clay	15	shale	995	bailing wtr		p.of
shale & shells	35	1BWH 995-1005		lime	1780	iron 3179
shale	60	lime	1035	shale wh	1790	to 88
red rock	75	shale	1045	lime	1865	shale 3195
shale	85	1 1/2 BWH 1045-55		shale	1870	lime 3205
lime	140	shale & shells	1050	1 BWPB 1825-30		Total Depth
shale & shells	170	lime	1085	shale & shells	1890	
lime	200	shale	1090	lime	1895	
shale	215	lime	1115	shale	1900	
lime(2BWPB 225-30)	235	shale	1125	lime	1915	HPW 302-05
shale	240	lime	1135	shale	1920	
reducing hole@240		shale	1145	lime	1925	Top
lime	250	lime	1160	lime brkn	1940	K.C.2053
shale	260	shale	1175	shale	2050	
lime	270	lime	1195	lime brkn	2055	
red rock	275	shale	1205	lime K.C.	2060	
lime	285	lime	1210	lime	2080	
shale	310	shale	1225	lime,caving	2100	
shale & shells	340	lime	1230	lime(2BW 2125-35)	2185	
lime	370	shale	1250	shale blk	2190	
shale	380	lime	1260	lime	2220	
lime	385	shale	1270	more wtr 2190-2210		
shale	430	lime	1275	shale	2230	
lime	435	shale	1295	lime	2300	
shale	500	sand	1305	shale blk	2325	
lime	510	HPW 1300-05		lime brkn	2335	
shale & shells	525	lime	1320	shale	2375	
shale	600	shale & shells	1330	lime	2400	
lime	615	shale	1350	shale & shells	2440	
shale	640	lime	1380	lime sdy	2445	
shale & shells	670	shale	1385	shale	2460	
lime	695	lime	1395	lime	2485	
shale	710	shale	1405	shale	2490	
lime	760	red rock	1415	lime	2525	
shale	765	lime	1440	shale	2575	
lime	770	hole caving 1405-15		lime	2600	
shale	790	shale	1450	shale	2620	
hole bad 785-90		lime	1455	sand	2630	
straightening same		shale	1490	shale	2720	
lime	795	lime	1495	Strung in@2710,		
filled hole up 25'		shale	1500	2710=2710;a trace of		
with rock & wire;		lime	1515	R.R. in run 2720-30		
drid out same;		shale	1520	shale & shells	2730	
hole OK at 795		shale sdy	1545	shale	2740	
lime	805	sand(HPW 1555)	1555	shale & shells	2772	
shale	815	shale	1665	sand	2775	
lime	820	HPW 1565-75		sand & chat	2779	
shale	850	sand	1605	lime	2820	
lime	855	shale	1620	lime blk	2915	
shale	870	no log	1625	lime W(1BWH 2930-	2930	
lime	885	shale sdy,bailing		lime 35)	3000	
shale	890	wtr	1660	lime brkn	3080	
lime	895	shale sdy	1690	lime	3105	
shale	900	lime brkn	1710	shale & shells	3120	
lime	910	hole making 4 BWH		lime	3130	
shale	915	between 1625-70		Corr.meas.3125=3124		
lime	925	shale	1720	shale	3150	
				shale blk	3188	