


Company- K. L. SCHOLFIELD
Farm- McKensie No. 1

SEC. 12 T. 30 R. 12E
SE SE SE

Total Depth. 1638
Comm. 7-30-52 Comp. 8-30-52
Shot or Treated.
Contractor. Shira Drilling Co.
Issued. 11-29-52

County Elk KANSAS



CASING:

4 1/2" 1601' cem.

Elevation. _____

Production. dry

Figures indicate Bottom of Formations.

soil rock, clay	20	lime	1623
sandrock	25	lime blk	1633
clay	30	lime HFW	1637
Set surface pipe @ 30'		Total Depth	1638
lime hard	40	Tops: Miss. Lime	1596
lime	65	Lane Wells Radioactivity	
shale shells	145	Log run.	
Pull 1st bit put on			
No. 2		Plugged 9-5-52	
shale	150		
lime brown	160		
shale	170		
lime broken	190		
shale, shells	300		
shale	360		
lime	370		
shale, shells	390		
lime	395		
shale	430		
sand	440		
shale	460		
lime	470		
shale, shells	480		
shale	525		
shale, shells	550		
lime	565		
shale	635		
shale, shells	660		
shale	695		
lime	755		
put on No 3 bit			
lime	825		
lime	830		
shale	850		
lime	955		
shale	965		
lime broken	985		
lime	1010		
shale	1025		
lime	1050		
shale, shells	1090		
sand	1110		
lime	1190		
Put on No 4 bit @ 1080			
shale	1210		
lime broken	1250		
shale, shells	1421		
red rock	1423		
shale, shells	1480		
shale red	1490		
shale, shells	1560		
Put on Bit No 5 @ 1455			
shells, sand	1596	Bit No. 5 Bald Headed	
Smell of Oil @ 1570			
sand, shale	1596		
lime Miss.	1601	RTD	
Drilling 1568 to 1589			
cement	1589		
Tailing in unit.			
Plug & cement	1601		
Shoe	1602		
lime brkn, blk shale	1620		