

~~30-22E-30-22E~~ 62
 30-22E-30-22E
 2-6
 Crawford Co.

Company Max B. Miller & Co., Inc.

Farm Smith No. 1 A


Total Depth 695'

Sec. 30 T. 30 R. 22

Comm. 1930

Comp. April, 1936

Loc. 600' from E line
 500' from S line
 SE $\frac{1}{4}$ -NE $\frac{1}{4}$



County Crawford

Elevation 905.29

Production

Figures Indicate Bottom of Formation

Soil	0	10
Lime	10	24
Black shale	24	29
Lime	29	42
Black shale	42	48
Lime	48	50
Light shale	50	61
Blue shale	61	105
Light shale	105	124
Dark shale	124	133
Light shale	133	143
Lime	143	146
Dark shale	146	154
Light shale	154	175
Sand	175	183
Light shale	183	218
Oil sand	218	265
Black shale	265	267
Light shale	267	280
Dark shale	280	295
Light shale	295	322
Light sandy shale	322	370
Dark shale	370	403
Grey sand	403	417
Light sandy shale	417	432
Dark shale	432	444
Light shale	444	451
Dark shale	451	497
Lime	497	501
Dark lime	501	506
Light grey hard lime	506	516
Dark grey hard lime	516	525
Dark grey coarse lime	525	530
Fine dark grey lime	530	538
Coarse dark grey lime	538	546
Coarse light grey lime	546	562
Fine light brown lime	562	609
Coarse light grey lime	609	632

N- 5256
 S- 5324
 E- 5328
 W- 5317
 2 2664 + 500 = 3164 FSL
 600 FEL

SE SE NE
 (K65-DEL NAD83)
 2022

10
 9
 5 Little gas
 8
 8
 16
 47

Sec. 30 30 South - 22 E

Company Max B. Miller & Co., Inc.

30-30-22E

Farm Smith No. 1A

(Continued)

Figures Indicate Bottom of Formation

Fine dark grey lime	632	645	13	
Fine light grey lime	645	660	35	
Coarse light grey lime	680	745	65	
Coarse dark grey lime	745	763	38	
Coarse light grey lime	783	812	29	
Shale	812	813	1	
Dark grey sand and white lime	813	819	6	
Green shale	819	822	3	
Dark grey sand	822	825	3	
Sandy shale	825	830	5	
Brown lime	830	835	5	
Light grey lime	835	840	5	
Dark grey lime	840	842	2	Water
Light grey lime	842	879	37	
Light brown lime	879	890	11	
Grey lime	890	895	5	