

Company Max B. Miller & Co., Inc.

19-30-22E

Farm Bevins N

No. Y

Total Depth 275'

Sec. 19 T. 30 R. 22

Comm. 10-11-39

Comp. 10-13-39

Loc. NW-NW-NE

County Crawford

Elevation 898.7'

Production

Figures Indicate Bottom of Formation

Top soil	0	2	2
Soft yellow clay	2	10	8
Soft dark shale	10	14	4
Soft light shale	14	60	45
Soft dark shale	60	69	9
Hard light lime	69	88	19
Soft dark shale	88	94	6
Hard light lime	94	105	11
Hard black shale	105	115	10
Soft light shale	115	130	15
Soft dark shale	130	150	20
Soft light shale	150	185	35
Soft dark shale	185	193	8
Hard light lime	193	194	1
Soft dark shale	194	208	14
Hard light lime	208	210	2
Soft black shale	210	215	5
Soft light shale	215	225	10
Soft dark shale	225	239	14
Soft light shale	239	273	34
Hard light sandy shale	273	275	2

Company Max B. Miller & Co., Inc.

19-30-22E

Farm Bevins N No. Y

Total Depth 275'

Sec. 19 T. 30 R. 22

Comm. 10-11-39

Comp. 10-13-39

Loc. NW-NW-NE

County Crawford

Elevation 898.7'

Production

Casing

130' 6 5/8"
314 2 5/8

10-17-39 Shot or Treated

77qts Gelatine	282'to 290'	Shells size	4" x 8' 6	16qts Elec.
	290 6 292 6			
	292 6 300		4 8 6	16qts
	300 315		5 15	45qts

Well not drilled through sand

Clean-Out record

Oct. 17-18-39 Cleaned with Larkin Sand Pump.