

C. L. CARLOCK
Starkey No. 1.

SEC. 21 T.30 R.7E
CSL SE SE
660' W 330' N SE cor.

Total Depth. 3194'

Comm. 3-20-40


Comp. 5-10-40

Shot or Treated.

Contractor.

Issued. 6-1-40

County. Cowley



CASING:

15 1/2" 126'
12 1/2" 1085'
10 " 1307' UR 1537'
8 " 2110'
7 " 2780' lowered to 2788'

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

cellar	10	lime sdy	1265	sh dead oil 2836-42
lime	35	sand	1280	sh free oil 2853-59
slate	40	lime	1298	trace of oil 3178-80
red rock	50	shale	1307	3 BWPH
lime	70	slate	1345	
slate	74	lime	1350	HF sulphur wtr 3185-94
lime	80	slate dk	1355	The hole was measured @ 2875'
shale	85	lime	1360	& found to be within 6" of
lime	125	shale	1380	being correct.
shale	130	red rock	1390	
red rock	132	slate	1398	All pipe pulled.
slate & shells	145	lime	1420	
lime	170	slate	1430	
slate	190	lime	1435	
lime	235	shale 3BW 1450-60	1445	
shale	240	lime	1480	
lime	245	shale	1505	
red rock	250	lime	1510	
lime	290	lime sdy	1535	
shale	295	lime	1547	
lime	310	shale	1635	
shale	315	lime HFW 1530	1855	
lime	320	shale 3BW 1742-50	1915	
shale	325	lime brown	1925	
lime	340	shale	2025	
shale	400	lime	2035	
lime	410	slate	2042	
shale	425	lime	2083	
lime	430	slate	2092	
shale	445	lime	2195	
lime	450	shale	2238	
shale & shells	480	lime	2285	
shale	575	slate dk	2318	
lime	580	lime	2322	
shale	620	shale	2326	
lime	635	lime	2330	
shale	655	slate lgt	2385	
lime	670	lime	2410	
shale	700	shale	2417	
lime	730	lime	2425	
shale	735	shale	2437	
red rock	740	lime	2442	
shale	825	shale	2470	
lime	850	lime	2493	
shale	870	shale	2498	
lime	890	lime	2526	
shale	970	slate	2532	
lime	1015	lime	2540	
shale	1025	shale	2620	
lime 6BW 1030-40	1084	lime sdy	2627	
shale	1095	shale	2815	
lime	1100	lime lgt	2890	
shale	1115	lime dk	2900	
lime	1125	lime sdy	2920	
shale	1135	lime dk	2995	
lime	1150	slate dk	2998	
shale	1160	lime lgt	3118	
lime	1175	slate blk	3178	
shale	1190	sand	3180	
lime	1195	lime sft	3194	
shale	1255	Total Depth.		