


THE GRIFFIN PROD CO & WILLIAM BELL
Oliver No. 10

SEC. 1 T. 32 R. 10 E.
Cen EL SE SW

Total Depth 1661½
Comm. 4-3-1935 Comp. 5-7-1935
Shot or Treated.
Contractor.
Issued. III-16-35

County- Chautauqua



CASING
Wood Conductor 3' 6 5/8" 1634'
12½" 380
10" 683
8½" 1324

Elevation

Production 30 bbls.

Figures Indicate Bottom of Formations.

soil	1	shale	1478
sand	4	lime	1491
lime	54	shale	1500
shale	66	lime	1508
red rock	74	shale	1578
lime	77	lime	1580
sand	90	shale	1584
shale	112	lime	1589
lime	114	Top of Pink lime	1589
shale blue	120	lime	1606
lime	130	shale black	1617
shale	152	shale white	1634
red rock	160	Oswego lime	1637
shale	220	lime gray	1641
sand	243	lime brown	1645
shale blue	250	lime gray hrd	1650
lime sdy	266	lime	1656
4 BW per hr 266		Some gas	1653
shale	276	lime	1660
lime	278	Bottom of Oswego	
shale	293	slate black	1661½
lime	317		
shale	321	Total Depth	1661½
lime	327		
shale	347		
sand sharp	358		
shale	360		
red rock	375		
shale drk	385		
lime	388		
shale	415		
sand 1 BW	425		
shale	463		
sand HFW	491		
shale	618		
lime	625		
shale blue	643		
sand	652		
shale	659		
sand	666		
shale	674		
sand	678		
shale	937		
lime	947		
shale	951		
lime brkn	963		
shale	1073		
lime	1077		
shale	1098		
sdv lime	1160		
sh le	1165		
s nd	1190		
lime	1200		
shale blue	1205		
lime	1270		
shale	1272		
lime	1280		
sand	1300		
sand	1342		
shale blue	1367		
lime sandy	1404		
shale drk	1427		
lime	1432		