

UNION NATIONAL BANK BLDG, WICHITA, KANSAS

SWc SW

Location. 250' fr S.L. 250' fr W.L. SWc

Sec. 29 T. 32 R. 10E

Casing Record.

County. Chautauqua.

10" Farm. Mary E. Stewart
 20" 8 1/2" Company. A. H. Craver.
 15" 65/8" Contr.
 12" 322 53/16" Comm. 7-24-28

No. 1

Comp. 9-25-28

Total Depth. 1597 Shot Quarts Between.

Correspondence Regarding This Well Should Be Referred To

Elevation.

Figures Indicate Bottom of Formations.

Initial Production. Dry

Date Issued. 1-2-32.

Formation	Depth	Formation	Depth.
soil brown soft	2	slate white soft	690
lime white hard	9	water sand white hard	752 HFW
shale blue soft	15	shale light soft	753
lime white hard	48	lime sdy light hard	756
shale blue soft	65	sand light hard	760
red rock red soft	70	broken lime light hard	775
lime white hard	80	shale blue soft	846
shale white soft	81	shale white soft	877 1/2 BW
red rock red soft	83	sdv lime light hard	882
sdv lime light hard	92	sdv shale white hard	895
shale white soft	95	sand white hard	900
red rock red soft	103	sdv lime white hard	905
shale blue soft	120	shale light soft	970
lime grey hard	132	lime light hard	975
shale blue soft	136	broken lime light hard	985
sdv shale light soft	140	shale white soft	1050
lime light hard	145	shale blk soft	1082
shale light soft	150	lime light hard	1090
sdv shale light soft	155	sdv shale light soft	1095
shale blue soft	195	lime hard	1101
sand light soft	206	broken lime light hard	1119
shale blue soft 10BW fresh wtr	210	shale blk soft	1131
sand light soft 210-37	235	gas sand light hard HFW	1201
shale white soft	237	sdv lime light hard	1203
sand light soft	258	shale dark soft	1210
shale blue soft	297	lime light hard	1214
lime light hard	320	shale dark soft	1216
shale blue soft	322	sdv lime light mod sh oil	1228
shale blue soft	330	broken shale light soft	1230
lime light hard	333	water sand light hard more wtr	1271
shale light soft	339	shale light soft	1274
red rock red soft	360	lime white hard	1287
shale blue soft	365	shale blue soft	1297
sand light hard 4BW	373	lime blue hard	1313
shale blue soft	380	shale blue soft	1315
sdv shale light soft	413	lime blue hard	1320
red rock red soft	416	shale blue soft	1330
lime light hard	432	lime white hard	1337
sdv fine light hard HFW	445	shale blue soft	1345
shale light soft	450	sdv lime light hard	1351
lime light hard	455	broken sand light hard	1373
shale light soft	470	shale blk soft	1378
lime light hard	475	lime white hard	1422
shale white soft	479	slate blk soft	1425
sand light mod.	510	lime light hard	1433
water increase.		shale blk soft	1451 cave
shale sd white soft	518	lime light hard	1452 S.L.
shale light soft	523	lime light hard	1462
sdv shale light hard	536	shale blk soft	1473
shale blue soft	550	lime light hard	1476
sand light hard	556	slate white soft	1478
shale blue soft	558	sdv lime grey hard	1486
lime light hard	564	Peru sand light hard	1525 Barren
shale blue soft	577	shale blue soft	1537
shale light soft	600	lime grey hard	1554
shale blue soft	625	shale green soft	1557
shale blk hard	630	lime light hard	1568
lime light hard	635	Wiser sand light hard 750 wtr	1593
shale dark soft	643	shale grey soft	1597 TD.
shale light hard	660		
shale light soft	677 1/2	Gas 1131-1201.	
coal blk soft	678 1/2	Peru 1486-1525	
		Wiser 1568-1593	