

UNION NATIONAL BANK BLDG, WICHITA, KANSAS

14-32-28 Plotted
CM

Location C EL SE NW/4

DEEPENING RECORD.


San. 14, 2, 32 R. 28.

220' fr EL 640' fr SL

Casing Record

County- Sumner.

10" 1350 Fara- L. B. Scroggins No. 3-A
20" 78 8 1/2" 1755 Company- Roxana Petroleum Corp.
15 1/2" 400 6 5/8" 2026 Contr.-
12 1/2" 950 5 3/16" Coma.- 8-18-28. Comp.- 9-17-28.



Total Depth: 2884 Shot 70 Quarts Between 2040-2073
Correspondence Regarding This Well Should Be Referred to

Figures Indicate Bottom of Formations.
Date Issued. 4-25-32.

Elevation Initial Production 73 bbls.
10 hrs.

APR 25 1936

Formation	Depth	Formation	Depth
sand	25	blue shale	1025
sandy lime	35	blue shale	1050
shale	95	line	1080
lime	100	shale	1130
sand	108	lime show oil 1/2 BOH	1135
sandy lime	120	shale	1140
blue shale	125	shale	1150
red rock	135	red rock	1165
lime	175	sandy shale show oil	1175
shale	180	shale	1185
lime	310	lime 1 BOH no water	1190
shale	320	shale	1247
shale	325	sft line	1250
red rock	335	hrd lime	1270
sandy lime	340	sandy lime	1283
shale	345	1 1/2 BOH at 1270-38'	
lime	355	shale	1300
shale	360	lime	1310
sandy lime Frest water	380	shale	1353
shale	388	lime	1360
red rock	400	shale	1370
lime	410	sandy shale	1380
shale	425	lime	1490
lime	445	Sho, oil at 1395' no water	
shale	450	black shale	1500
lime	495	lime little water	1520
shale	500	shale	1525
lime	510	lime	1580
sandy shale	525	sandy lime	1570
lime	530	shale	1585
red rock	560	sand show oil & H ₂ O	1610
lime Water at 575'	600	shale	1615
black shale	640	shelly lime	1620
lime	655	shale	1625
sandy shale	670	lime	1630
lime 2 1/2 BOH at 700'	700	shale	1650
shale	710	sandy lime	1680
lime	720	shale	1695
black shale	725	sand water	1715
lime	745	shale	1745
blue shale	755	shale	1746
light shale	770	lime	1755
lime	780	shale	1760
sandy lime	785	shale	1765
Small show oil		sandy shale	1800
blue shale	795	shale	1846
shale	845	Sho oil at 1800'	
sandy lime 1/2 BOH	865	lime	1850
shale	870	shale	1985
lime	875	shale & shells	2025
shale	395	sandy shale	2027
lime Little oil	905	Show oil 75' in 24 hrs.	
shale	915	SLC	2026
sandy lime 5 BOH	920	sandy lime	2034
shale	928	sand & shale	2073
lime	930	SLC	2071
shale	948	sand & shale	2074
shale & shells	950	sand	2076
shale	965	SLC	2080
lime	970	Total Depth	2080'

Shell Petroleum Corp.
 L.B. Groggins No. A-3
 14-32-2E.

Computer Inventoried

Page 2

DEEPENING RECORD.

Comm. 3-33-36 Comp. 4-8-36
 Prod. Pot. 740 B.
 Casing 21 1/2" 78'
 10 3/4" 1350'
 7" 2836'

Plugged back to sand	2076	
sand		2120
sand and shale		2170
shale		2350
shale		2402
lime with shale breaks		2415
2415 equals 2417 SLC		
shale		2425
lime		2442
lime and shale		2444
lime		2560
lime		2582
shale and lime shells		2593
lime		2623
shale and lime shells		2674
lime		2687
lime		2690
shale and lime shells		2705
lime		2745
shale and lime shells		2812
broken lime		2820
shale and lime		2824
shy shale		2835
dolomite		2839
dolomite		2867
200' oil in 1 1/2 hours	2842	
600' oil in hole in 4 hrs	2845.	
1000' oil in hole in 6 hrs	2845'	
2000' oil in hole 20 1/2 hrs.	2859.	
dolomite soft		2870
dolomite hard		2873
dolomite		2878
sand		2881
sand		2884
Total Depth.		