

G

Company: Eagle-Picher

Sec. 36 T. 32 R. 24

Farm: C. W. Hiller

No. 2

Loc. SWc SW SE

Comm. January 15, 1943

County: Cherokee

Comp. January 22, 1943

Total Depth: 323

Contractor: Fort & George

Water Level: 150

Driller: Lloyd George

Elevation: 890

Formation

	Thickness	Depth
soil and clay	15	15
soapstone	5	20
soapstone and some coal	5	25
soapstone	40	65
sandstone	20	85
soapstone	15	100
flint, gray and light gray; mundic	10	110
lime, gray; flint, gray and light gray	10	120
lime, tan; flint, gray, dark gray and blue	5	125
lime, tan; flint, gray and dark gray; selvage, gray and green	5	130
tan lime; flint, gray	5	135
lime, gray; flint, gray	5	140
flint, gray and light gray	20	160
lime, gray; flint, gray and brown speckled	10	170
lime, brown; flint, gray	10	180
lime, tan and gray; flint, gray	15	195
lime, tan; flint, gray	35	230
lime, brown; flint, gray	15	245
flint, gray and light gray	25	270
flint, gray, light and pale blue flint	5	275
jasperoid, brown; flint, gray, dark gray and blue	15	290
jasperoid, brown and gray; flint, gray, dark gray and blue	30	320
lime, gray; jasperoid, gray; flint, dark gray and blue	3	323

Strong water at 20 ft.
Set 43' of 6 $\frac{1}{4}$ pipe
Little water at 100 ft.
Strong at 260 ft.