

4-32-5E

LEASE	WELL NO.	COUNTY
Elrod	1	Cowley, Kans.
DRILLED	330' from N. line and	LOCATION
Arkansas Nat. (?)	330' from E. line	N/2 of SW/4
INITIAL PRODUCTION		SEC.
ROCK PRESSURE		T. 4
ELEVATION		R. 32
DRILLING COMMENCED		5
TOTAL DEPTH		COMPLETED

FORMATION	TOP	BOTTOM	FORMATION	TOP	BOTTOM
1			1		
2			2		
3			3		
4			4		
5			5		
6			6		
7			7		
8			8		
9			9		
10			10		
11			11		
12			12		
13			13		
14			14		
15			15		
16			16		
17			17		
18			18		
19			19		
20			20		
21			21		
22			22		
23			23		
24			24		
25			25		
26			26		
27			27		
28			28		
29			29		
30			30		
31			31		
32			32		
33			33		
34			34		
35			35		
36			36		
37			37		
38			38		
39			39		
40			40		
41			41		
42			42		
43			43		
44			44		
45			45		
46			46		
47			47		
48			48		
49			49		
50			50		
51			51		
52			52		
53			53		
54			54		
55			55		
56			56		
57			57		
58			58		
59			59		
60			60		
61			61		
62			62		
63			63		
64			64		
65			65		
66			66		
67			67		
68			68		
69			69		
70			70		
71			71		
72			72		
73			73		
74			74		
75			75		
76			76		
77			77		
78			78		
79			79		
80			80		
81			81		
82			82		
83			83		
84			84		
85			85		
86			86		
87			87		
88			88		
89			89		
90			90		
91			91		
92			92		
93			93		
94			94		
95					

Soil black soft	2
Red rock soft	60
Shelly white soft	80
Shale	125
Shale black soft	150
Water sand white hard	170 From 150 to 170 H. F. W.
Shale black soft	175
Lime white hard	200
Shale black soft	205
Red rock soft	215
Slate black soft	275
Lime white hard	285
Slate blue soft	290
Lime white hard	325 295 - 3 blrs.
Slate black soft	335
Red rock soft	345
Lime white hard	395
Slate black soft	400
Lime white hard	420
Red rock soft	450
Lime hard	550
Red rock soft	570
Red rock soft	595
Lime white hard	625
Slate black soft	630
Lime white hard	640
Shale white soft	645
Red rock soft	655
Lime & sand white hard	665 H. F. W.
Sand white soft	680
Slate blue soft	730
Lime white hard	750
Slate white soft	800
Slate blue soft	810
Sand white soft	820 H. F. W.
Slate dark soft	835
Lime white soft	845
Slate blue soft	855
Lime white hard	865
Red rock soft	870
Slate white soft	890
Slate dark	900
Sand white soft	915 4 blrs.
Slate black soft	925
Lime white soft	935
Shale black soft	945
Sand white soft	950
Slate blue soft	960
Slate dark soft	1015
Lime white dark	1025
Slate blue soft	1030
Lime white hard	1065
Slate dark soft	1090
Lime white hard	1100
Slate dark soft	1130
Lime gray hard	1140
Slate dark soft	1165
Lime white hard	1175
Shale dark soft	1220
Lime gray hard	1230
Slate white soft	1235
Lime gray hard	1245
Slate black soft	1255
Lime sandy soft	1275 H. F. W.
Lime white hard	1280
Slate black soft	1290
Lime gray hard	1300

(OVER)

Slate dark soft	1350	
Lime white hard	1360	
Slate white soft	1375	
Lime white hard	1380	
Slate white soft	1385	
Lime white hard	1410	
Slate light soft	1450	
Slate dark soft	1460	
Lime gray hard	1500	
Slate white soft	1505	
Lime white hard	1580	
Slate dark soft	1600	2 blrs. water at 1595.
Sandy soft	1620	
Slate white soft	1640	
Slate dark soft	1700	
Slate light soft	1720	
Lime gray hard	1740	
Slate dark soft	1760	Cave at 1760
Lime white hard	1765	
Sand white soft	1780	H. F. W.
Slate white soft	1830	
Lime white hard	1840	
Slate dark soft	2000	
Slate white soft	2015	
Sand white soft	2035	
Slate dark soft	2055	
Sand light soft	2110	H. F. W. at 2070.
TOTAL DEPTH	3100	plus.