

26-33-11E

SINCLAIR PRAIRIE OIL CO.
H.S. Lantz No. 13

SEC. 26 T. 33 R. 11E.
NW NE SW
1180' fr EL. 1045' fr SL N $\frac{1}{2}$ SW $\frac{1}{4}$


Total Depth. 1168
Comm. 11-28-38 Comp. 12-16-38
Shot or Treated. 50 qts 1125-41
Contractor. Locke Drilling Co.
Issued. 1-14-39

County Chautauqua.

JAN 14 1939

CASING.

105/8" 10'
85/8" 200'
7" 1006'
2" tubing 1160'



Elevation.

Production. 3 bbls.,
after shot.

Figures Indicate Bottom of Formations.

clay surface	25
lime	28
shale	60
lime sdy	85
shale	95
lime	105
shale	110
lime	118
shale	180
lime	183
shale	187
lime	190
shale	244
lime	250
shale salt water	275
sand	310
lime	315
shale	455
sand salt water	500
shale	527
lime	540
sand salt water	550
shale	600
lime	603
shale	640
lime	647
shale	780
sand	782
shale	790
lime	795
shale	805
sand	860
shale	930
lime	937
shale	942
sand	1002
shale	1095
lime	1096
shale	1105
lime	1107
shale	1112
lime	1121
shale	1127
sand	1141
shale	1168

Peru sand 1127-1141

Total Depth.